


- CONNECTOR MATES WITH ANY 9 POSN PLUG IN AMPLIMITE SERIES & COMPLIES WITH AMP SPEC 108-40005 WHERE APPLICABLE.
- ▲ MOLDED PARTS: FLAME RETARDANT 94V-0 RATED THERMOPLASTIC, COLOR: SEE TABLE.
 SHELL: CARBON STEEL
 CONTACTS: PHOSPHOR BRONZE
 EYELETS: BRASS
 SCREWLOCKS: ZINC
 INSERTS: ZINC
 - ▲ SHELL: TIN PLATED
 CONTACTS: SEE TABLE
 EYELETS: TIN PLATED
 SCREWLOCKS: CLEAR CHROMATE
 INSERTS: CLEAR CHROMATE
 - ▲ GOLD FLASH FOR A DISTANCE OF .100 MIN FROM MATING END, TIN PLATED .000100-.000200 ON OPPOSITE END, ALL OVER .000050 NICKEL.
 - ▲ .000030 GOLD FOR A DISTANCE OF .100 MIN FROM MATING END, TIN PLATED .000100-.000200 ON OPPOSITE END, ALL OVER .000050 NICKEL.



AQUA (TURQUOISE)	THREADED INSERTS	▲	5745781-7
BLACK	FEMALE SCREWLOCKS	▲	5745781-6
BLACK	THREADED INSERTS	▲	5745781-4
BLACK	THREADED INSERTS	▲	5745781-3
BLACK	NONE	▲	5745781-2
COLOR	MOUNTING HARDWARE	CONTACT FINISH	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. **TE Connectivity**

DESIGNED BY: J. FERNANDEZ-000025	DATE: 06-28-21	REVISED BY: M. WILMSLEY	DATE: 06-28-21
APPROVED BY: [Signature]			
DESCRIPTION: RCPT ASSY, SIZE 1, 9 POSN, RTANG, AMPLIMITE HD-20, WITH METAL SHELL, WITH OR WITHOUT SCREWLOCKS OR INSERTS			
REV: 1	DATE: 06-28-21	REV: 1	DATE: 06-28-21
REV: 2	DATE: 06-28-21	REV: 2	DATE: 06-28-21
REV: 3	DATE: 06-28-21	REV: 3	DATE: 06-28-21
REV: 4	DATE: 06-28-21	REV: 4	DATE: 06-28-21
REV: 5	DATE: 06-28-21	REV: 5	DATE: 06-28-21
REV: 6	DATE: 06-28-21	REV: 6	DATE: 06-28-21
REV: 7	DATE: 06-28-21	REV: 7	DATE: 06-28-21
REV: 8	DATE: 06-28-21	REV: 8	DATE: 06-28-21
REV: 9	DATE: 06-28-21	REV: 9	DATE: 06-28-21
REV: 10	DATE: 06-28-21	REV: 10	DATE: 06-28-21

CUSTOMER DRAWING SIZE: 4.1 SHEET: 1 OF 1 REV: A1