



- △ FLAME RETARDANT, 94V-0 RATED, GLASS FILLED, NYLON OR POLYESTER, COLOR: BLACK.
- △ PHOS. BRONZE PER QQ-B-750.
- △ REFER TO APPLICATION SPEC FOR RECOMMENDED P.C. BOARD MOUNTING DIMENSIONS FOR AUTOMATIC INSERTION.
- △ ZINC.
- △ GOLD PLATING PER MIL-G-45204, TIN PLATING PER MIL-T-10727, NICKEL PLATING PER QQ-N-290.
- △ CLEAR CHROMATE.
- △ PLATED WITH GOLD FLASH FOR LENGTH OF .055 MIN FROM MATING END, WITH POINT OF MEASUREMENT .035 FROM MATING END OF CONTACT, .000100-.000200 TIN OR TIN-LEAD ON SOLDER END, ALL OVER .000050 NICKEL ON ENTIRE CONTACT.
- △ PLATED WITH .000030 GOLD FOR LENGTH OF .055 MIN FROM MATING END, WITH POINT OF MEASUREMENT .035 FROM MATING END OF CONTACT, .000100-.000200 TIN OR TIN-LEAD ON SOLDER END, ALL OVER .000050 NICKEL ON ENTIRE CONTACT.
- △ PLATED WITH .000010 GOLD FOR LENGTH OF .055 MIN FROM MATING END, WITH POINT OF MEASUREMENT .035 FROM MATING END OF CONTACT, .000100-.000200 TIN OR TIN-LEAD ON SOLDER END, ALL OVER .000050 NICKEL ON ENTIRE CONTACT.

OBSOLETE	WITH INSERTS	△	747461-7
OBSOLETE	WITH SCREWLOCKS	△	747461-6
OBSOLETE	WITH SCREWLOCKS	△	747461-5
OBSOLETE	WITH INSERTS	△	747461-4
OBSOLETE	WITH INSERTS	△	747461-3
	WITH .120 DIA HOLE	△	747461-2
	WITH .120 DIA HOLE	△	747461-1

THIS DRAWING IS A CONTROLLED DOCUMENT. REVISED: 7-28-87

DESIGNED BY: J. B. WELDON
CHECKED BY: J. B. WELDON

RECEPTACLE ASSY, SIZE 3, 25 POSN, RIGHT ANGLE, 590 SERIES, .026 DIA POSTS, AMPLIMATE HC-00

REV: 1
DATE: 08/15/87
DRAWN BY: A1
CHECKED BY: 00779
C=747461

CUSTOMER DRAWING