



Directive 2002/95/EC  
RoHS  
Compliant

NOTES:

1. METALSHIELDS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; GREEN
3. HIGH POWER CONTACTS 30A: COPPER ALLOY  
PLATING MATING AREA: 30µin HARD GOLD over min. 50µin NICKEL  
PLATING TERMINATION SIDE: 8µin HARD GOLD over min. 50µin NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 10-12  
FEMALE CONTACT ON POS. A1 and A2
4. SIGNAL CONTACTS: COPPER ALLOY; 7,5A nominal  
PLATING MATING AREA: 30µin HARD GOLD over min. 50µin NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 20  
FEMALE CONTACTS WIRE BRIDGE FROM POS. 1 TO POS. 2,  
NO CONTACTS ON POS. 3, 4, 5
5. CONNECTOR IS PART MARKED: 13-000161 CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND

1 x b	Ä3392	31.07.09	Sonne
a	Origin		
rev.	description	date	name

tolerance		dim. in mm
date	name	
drawn	19.06.07	Schmidt
appd.	19.06.07	Koch
norm		
d-old		

scale:	2:1 (5:1)	
material:	see notes	
title:		
Micro TCA Single Port		
Female, Solder Cup for cable AWG 10 - 12 with wire bridge on signal contacts		
dwg no:	Inventor 10	DIN-A3
	13K1A2071	sh: 1
part no:	13-000161	

