



- △ FLAME RETARDANT, 94V-0 RATED, GLASS FILLED, NYLON OR POLYESTER, COLOR: BLACK.
- △ PHOS. BRONZE PER QQ-B-750.
- △ REFER TO APPLICATION SPEC FOR RECOMMENDED P.C. BOARD MOUNTING DIMENSIONS FOR AUTOMATIC INSERTION.
- △ ZINC.
- △ GOLD PLATING PER MIL-G-45204, TIN PLATING PER MIL-T-10727, NICKEL PLATING PER QQ-N-290.
- △ CLEAR CHROMATE.
- △ PLATED WITH GOLD FLASH FOR LENGTH OF .055 MIN FROM MATING END, WITH POINT OF MEASUREMENT .035 FROM MATING END OF CONTACT. .000100-.000200 TIN OR TIN-LEAD ON SOLDER END, ALL OVER .000050 NICKEL ON ENTIRE CONTACT.
- △ PLATED WITH .000030 GOLD FOR LENGTH OF .055 MIN FROM MATING END, WITH POINT OF MEASUREMENT .035 FROM MATING END OF CONTACT. .000100-.000200 TIN OR TIN-LEAD ON SOLDER END, ALL OVER .000050 NICKEL ON ENTIRE CONTACT.

SUPSD BY 74B94B-1	WITH SCREWLOCKS	△	747460-6
	WITH SCREWLOCKS	△	747460-5
	WITH INSERTS	△	747460-4
	WITH INSERTS	△	747460-3
	WITH .120 DIA HOLE	△	747460-2
	WITH .120 DIA HOLE	△	747460-1

REMARKS		FINISH	PART NUMBER
THIS DRAWING IS A CONTROLLED DOCUMENT.			
DESIGNED BY	REVISIONS		
DRAWN BY	DATE		
CHECKED BY	APPROVED BY		
DATE			
CUSTOMER DRAWING			