



- △ MATERIAL:
 PIN CONTACTS- PHOSPHOR BRONZE.
 PLUG SHELL- STEEL.
 PLUG HOUSING AND TERMINATION COVERS- UL V-0 RATED POLYESTER THERMOPLASTIC.
 COLOR: BLACK.
- △ PLATING:
 PIN CONTACTS- 0.00076 [.000030] MINIMUM GOLD PLATE IN LOCALIZED GOLD PLATE AREA, 0.00127 [.000050] MINIMUM BRIGHT TIN-LEAD PLATE IN TERMINATION AREA, ALL OVER 0.00127 [.000050] MINIMUM NICKEL.
 PLUG SHELL- 0.00508 [.000200] MINIMUM BRIGHT TIN-LEAD PLATE OVER 0.00127 [.000050] MINIMUM COPPER.
- △ TERMINATION COVERS ARE PACKAGED SEPARATELY.
4. DIMENSIONS IN BRACKETS ARE IN INCHES.
5. RECOMMENDED WIRE:
 28 AWG- 0.81 [.032] MAX O.D. PVC OR POLYETHYLENE INSULATION.
- △ PLATING:
 PIN CONTACTS- GOLD FLASH OVER 0.001[.000040] MIN PALLADIUM NICKEL PLATE IN LOCALIZED GOLD PLATE AREA, 0.00127 [.000050] MINIMUM BRIGHT TIN PLATE IN TERMINATION AREA, ALL OVER 0.00127 [.000050] MINIMUM NICKEL.
 PLUG SHELL- 0.00508 [.000200] MINIMUM BRIGHT TIN PLATE OVER 0.00127 [.000050] MINIMUM COPPER.

OBSOLETE	△	750833-2
	△	750833-1
FINISH		PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DESIGNED BY	DATE	APPROVED BY	DATE
DR			
DESIGNED BY	DATE	APPROVED BY	DATE
DR			
DESIGNED BY	DATE	APPROVED BY	DATE
DR			

AMP Electronics
 Harrisburg, PA 17105-3008

PLUG KIT,CABLE CONNECTOR,26 POSITION,
 TM

SIZE: A1 DATE REE: 000779 DRAWING NO: 750833
 CUSTOMER DRAWING

REVISED TO: ---

SCALE: 2:1 SHEET: 1 OF 1