

MAXIM

Ultra-High-Precision SOT23 Series Voltage Reference

MAX6033

General Description

The MAX6033 ultra-high-precision series voltage reference features a low 7ppm/ $^{\circ}\text{C}$ (max) temperature coefficient and a low dropout voltage (200mV, max). Low temperature drift and low noise make the MAX6033 ideal for use with high-resolution ADCs or DACs.


This device uses bandgap technology for low-noise performance and excellent accuracy. Laser-trimmed, high-stability, thin-film resistors, and postpackage trimming guarantee excellent initial accuracy ($\pm 0.04\%$, max). The MAX6033 consumes only 40 μA of supply current and sources up to 15mA. Series mode references save system power and use minimal external components compared to two-terminal shunt references.

The MAX6033 is available in the miniature 6-pin SOT23 package and is offered over the automotive temperature range (-40 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$).

Applications

- Precision Regulators
- A/D and D/A Converters
- Power Supplies
- Hard-Disk Drives
- High-Accuracy Industrial and Process Control
- Hand-Held Instruments

Typical Operating Circuit



Features

- ◆ Tiny 6-Pin SOT23 Package
- ◆ Ultra-Low Temperature Drift: 7ppm/ $^{\circ}\text{C}$ (max)
- ◆ $\pm 0.04\%$ Initial Accuracy
- ◆ Stable with Capacitive Loads
- ◆ Low 16 $\mu\text{Vp-p}$ Noise (0.1Hz to 10Hz) (2.5V Output)
- ◆ 15mA Output Source Current
- ◆ Low 200mV Dropout Voltage
- ◆ Low 40 μA Quiescent Current
- ◆ Wide 2.7V to 12.6V Supply Voltage
- ◆ Excellent Load Regulation: 0.001mV/mA

Ordering Information


PART	TEMP RANGE	PIN-PACKAGE
MAX6033AAUT_ -T	-40 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$	6 SOT23-6
MAX6033BAUT_ -T	-40 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$	6 SOT23-6
MAX6033CAUT_ -T	-40 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$	6 SOT23-6

Note: Two-number part suffix indicates output voltage option.
SOT23 Package Top Marks appear at end of data sheet.

Selector Guide

SUFFIX	VOLTAGE OUTPUT
25	2.500V
30	3.000V
41	4.096V
50	5.000V

Pin Configuration



MAXIM

Maxim Integrated Products 1

For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at www.maxim-ic.com.

Ultra-High-Precision SOT23 Series Voltage Reference

ABSOLUTE MAXIMUM RATINGS

IN to GND -0.3V to +13V
 OUTF, OUTS to GND -0.3V to +6V
 Continuous Power Dissipation ($T_A = +70^\circ\text{C}$) 6-Pin SOT23 (derate 9.1mW/ $^\circ\text{C}$ above $+70^\circ\text{C}$) 727mW

Operating Temperature Range -40°C to $+125^\circ\text{C}$
 Storage Temperature Range -65°C to $+150^\circ\text{C}$
 Maximum Junction Temperature $+150^\circ\text{C}$
 Lead Temperature (soldering, 10s) $+300^\circ\text{C}$

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS— $V_{\text{OUT}} = 2.500\text{V}$

($V_{\text{IN}} = 5\text{V}$, $C_{\text{OUT}} = 0.1\mu\text{F}$, $I_{\text{OUT}} = 0$, $T_A = T_{\text{MIN}}$ to T_{MAX} , unless otherwise specified. Typical values are at $T_A = +25^\circ\text{C}$.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Output Voltage	V_{OUT}	$T_A = +25^\circ\text{C}$	MAX6033A	2.4990	2.5000	2.5010	V
			MAX6033B	2.4950	2.5000	2.5050	
			MAX6033C	2.4975	2.5000	2.5025	
Output-Voltage Accuracy		$T_A = +25^\circ\text{C}$	MAX6033A	-0.04		+0.04	%
			MAX6033B	-0.2		+0.2	
			MAX6033C	-0.1		+0.1	
Output Voltage Temperature Coefficient	TCV_{OUT}	MAX6033A	$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$	1.5	7		ppm/ $^\circ\text{C}$
			$T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$	2.5	10		
		MAX6033B	$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$	3	10		
			$T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$	7	15		
		MAX6033C	$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$	6	20		
			$T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$	10	40		
Input Voltage Range	V_{IN}	Inferred from line regulation specification		2.7	12.6		V
Line Regulation	$\Delta V_{\text{OUT}}/\Delta V_{\text{IN}}$	$2.7\text{V} \leq V_{\text{IN}} \leq 12.6\text{V}$	$T_A = +25^\circ\text{C}$	3	25		$\mu\text{V/V}$
			$T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$		50		
Load Regulation	$\Delta V_{\text{OUT}}/\Delta I_{\text{OUT}}$	$-100\mu\text{A} \leq I_{\text{OUT}} \leq 15\text{mA}$	$T_A = +25^\circ\text{C}$	0.001	0.05		mV/mA
			$T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$		0.1		
Dropout Voltage (Note 2)	V_{DO}	$V_{\text{OUT}} = 0.1\%$, $I_{\text{OUT}} = 1\text{mA}$		0.02	0.2		V
		$V_{\text{OUT}} = 0.1\%$, $I_{\text{OUT}} = 10\text{mA}$	$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$	0.3	0.4		
			$T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$		0.5		
Quiescent Supply Current	I_{IN}	$T_A = +25^\circ\text{C}$		40	60		μA
		$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$			75		
		$T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$			85		
Output Short-Circuit Current	I_{SC}	$V_{\text{OUT}} = 0$		90			mA
		$V_{\text{OUT}} = V_{\text{IN}}$		-2			
Output-Voltage Noise	e_n	$0.1\text{Hz} \leq f \leq 10\text{Hz}$		16			$\mu\text{V}_{\text{P-P}}$
		$10\text{Hz} \leq f \leq 1\text{kHz}$		12			
Turn-On Settling Time	t_{ON}	V_{OUT} settles to $\pm 0.01\%$ of final value		500			μs
Temperature Hysteresis		(Note 3)		150			ppm
Long-Term Stability		$\Delta t = 1000\text{hr}$		40			ppm

Ultra-High-Precision SOT23 Series Voltage Reference

ELECTRICAL CHARACTERISTICS—V_{OUT} = 3.000V

(V_{IN} = 5V, C_{OUT} = 0.1μF, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6033A	2.9988	3.0000	3.0012	V
			MAX6033B	2.9940	3.0000	3.0060	
			MAX6033C	2.9970	3.0000	3.0030	
Output-Voltage Accuracy		T _A = +25°C	MAX6033A	-0.04	+0.04	+0.04	%
			MAX6033B	-0.2	+0.2	+0.2	
			MAX6033C	-0.1	+0.1	+0.1	
Output-Voltage Temperature Coefficient	TCV _{OUT}	MAX6033A	T _A = -40°C to +85°C	1.5	7	7	ppm/°C
			T _A = -40°C to +125°C	2.5	10	10	
		MAX6033B	T _A = -40°C to +85°C	3	10	10	
			T _A = -40°C to +125°C	7	15	15	
		MAX6033C	T _A = -40°C to +85°C	6	20	20	
			T _A = -40°C to +125°C	10	40	40	
Input Voltage Range	V _{IN}	Inferred from line regulation specification		3.2	12.6	12.6	V
Line Regulation	ΔV _{OUT} / ΔV _{IN}	3.2V ≤ V _{IN} ≤ 12.6V	T _A = +25°C	4	30	30	μV/V
			T _A = -40°C to +125°C	60		60	
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	-100μA ≤ I _{OUT} ≤ 15mA	T _A = +25°C	0.002	0.06	0.06	mV/mA
			T _A = -40°C to +125°C	0.12		0.12	
Dropout Voltage (Note 2)	V _{DO}	ΔV _{OUT} = 0.1%	I _{OUT} = 1mA	0.02	0.2	0.2	V
			I _{OUT} = 10mA	0.2	0.4	0.4	
Quiescent Supply Current	I _{IN}	T _A = +25°C		40	60	60	μA
		T _A = -40°C to +85°C		75		75	
		T _A = -40°C to +125°C		85		85	
Output Short-Circuit Current	I _{SC}	V _{OUT} = 0		90		90	mA
		V _{OUT} = V _{IN}		-2		-2	
Output-Voltage Noise	e _n	0.1Hz ≤ f ≤ 10Hz		24		24	μV _{P-P}
		10Hz ≤ f ≤ 1kHz		15		15	
Turn-On Settling Time	t _{ON}	V _{OUT} settles to ±0.01% of final value		600		600	μs
Temperature Hysteresis		(Note 3)		150		150	ppm
Long-Term Stability		Δt = 1000hr		40		40	ppm

ELECTRICAL CHARACTERISTICS—V_{OUT} = 4.096V

(V_{IN} = 5V, C_{OUT} = 0.1μF, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6033A	4.0943	4.0960	4.0977	V
			MAX6033B	4.0878	4.0960	4.1042	
			MAX6033C	4.0919	4.0960	4.1001	
Output-Voltage Accuracy		T _A = +25°C	MAX6033A	-0.04	+0.04	+0.04	%
			MAX6033B	-0.2	+0.2	+0.2	
			MAX6033C	-0.1	+0.1	+0.1	

MAX6033

Ultra-High-Precision SOT23 Series Voltage Reference

ELECTRICAL CHARACTERISTICS—V_{OUT} = 4.096V (continued)

(V_{IN} = 5V, C_{OUT} = 0.1μF, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Output-Voltage Temperature Coefficient	TCV _{OUT}	MAX6033A	T _A = -40°C to +85°C	1.5	7		ppm/°C
			T _A = -40°C to +125°C	2.5	10		
		MAX6033B	T _A = -40°C to +85°C	3	10		
			T _A = -40°C to +125°C	7	15		
		MAX6033C	T _A = -40°C to +85°C	6	20		
			T _A = -40°C to +125°C	10	40		
Input-Voltage Range	V _{IN}	Inferred from line regulation specification		4.3		12.6	V
Line Regulation	ΔV _{OUT} / ΔV _{IN}	4.3V ≤ V _{IN} ≤ 12.6V	T _A = +25°C	6	30		μV/V
			T _A = -40°C to +125°C		60		
Load Regulation	ΔV _{OUT} / ΔI _{OUT}	-100μA ≤ I _{OUT} ≤ 15mA	T _A = +25°C	0.002	0.08		mV/mA
			T _A = -40°C to +125°C		0.15		
Dropout Voltage (Note 2)	V _{DO}	ΔV _{OUT} = 0.1%	I _{OUT} = 1mA	0.02	0.2		V
			I _{OUT} = 10mA	0.2	0.4		
Quiescent Supply Current	I _{IN}	T _A = +25°C		40	60		μA
		T _A = -40°C to +85°C			75		
		T _A = -40°C to +125°C			85		
Output Short-Circuit Current	I _{SC}	V _{OUT} = 0		90			mA
		V _{OUT} = V _{IN}		-2			
Output-Voltage Noise	e _n	0.1Hz ≤ f ≤ 10Hz		32			μVP-P
		10Hz ≤ f ≤ 1kHz		22			
Turn-On Settling Time	t _{ON}	V _{OUT} settles to ±0.01% of final value		800			μs
Temperature Hysteresis		(Note 3)			150		ppm
Long-Term Stability		Δt = 1000hr			40		ppm

ELECTRICAL CHARACTERISTICS—V_{OUT} = 5.000V

(V_{IN} = 5.5V, C_{OUT} = 0.1μF, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	T _A = +25°C	MAX6033A	4.9980	5.000	5.0020	V
			MAX6033B	4.9900	5.000	5.0100	
			MAX6033C	4.9950	5.000	5.0050	
Output-Voltage Accuracy		T _A = +25°C	MAX6033A	-0.04		+0.04	%
			MAX6033B	-0.2		+0.2	
			MAX6033C	-0.1		+0.1	
Output-Voltage Temperature Coefficient	TCV _{OUT}	MAX6033A	T _A = -40°C to +85°C	1.5	7		ppm/°C
			T _A = -40°C to +125°C	2.5	10		
		MAX6033B	T _A = -40°C to +85°C	3	10		
			T _A = -40°C to +125°C	7	15		
		MAX6033C	T _A = -40°C to +85°C	6	20		
			T _A = -40°C to +125°C	10	40		
Input Voltage Range	V _{IN}	Inferred from line regulation specification		5.2		12.6	V

Ultra-High-Precision SOT23 Series Voltage Reference

ELECTRICAL CHARACTERISTICS—V_{OUT} = 5.000V (continued)

(V_{IN} = 5.5V, C_{OUT} = 0.1μF, I_{OUT} = 0, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at T_A = +25°C.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Line Regulation	$\Delta V_{OUT}/\Delta V_{IN}$	5.2V ≤ V _{IN} ≤ 12.6V	T _A = +25°C	7	50	μV/V
			T _A = -40°C to +125°C		100	
Load Regulation	$\Delta V_{OUT}/\Delta I_{OUT}$	-100μA ≤ I _{OUT} ≤ 15mA	T _A = +25°C	0.003	0.1	mV/mA
			T _A = -40°C to +125°C		0.2	
Dropout Voltage (Note 2)	V _{DO}	ΔV _{OUT} = 0.1%	I _{OUT} = 1mA	0.02	0.2	V
			I _{OUT} = 10mA	0.2	0.4	
Quiescent Supply Current	I _{IN}	T _A = +25°C		40	60	μA
		T _A = -40°C to +85°C			75	
		T _A = -40°C to +125°C			85	
Output Short-Circuit Current	I _{SC}	V _{OUT} = 0		90		mA
		V _{OUT} = V _{IN}		-2		
Output-Voltage Noise	e _n	0.1Hz ≤ f ≤ 10Hz		40		μVP-P
		10Hz ≤ f ≤ 1kHz		26		
Turn-On Settling Time	t _{ON}	V _{OUT} settles to ±0.01% of final value		1000		μs
Temperature Hysteresis		(Note 3)		150		ppm
Long-Term Stability		Δt = 1000hr		40		ppm




Note 1: MAX6033 is 100% production tested at T_A = +25°C and is guaranteed by design for T_A = T_{MIN} to T_{MAX} as specified.

Note 2: Dropout Voltage is the minimum input voltage at which V_{OUT} changes ≤ 0.1% from V_{OUT} at V_{IN} = 5V (V_{IN} = 5.5V for V_{OUT} = 5V).

Note 3: Temperature Hysteresis is defined as the change in +25°C output voltage before and after cycling the device from T_{MAX} to T_{MIN}.

Typical Operating Characteristics

(V_{IN} = 5V, C_{OUT} = 0.1μF, I_{OUT} = 0, T_A = +25°C, unless otherwise specified.) (Note 4)




Ultra-High-Precision SOT23 Series Voltage Reference


Typical Operating Characteristics (continued)

($V_{IN} = 5V$, $C_{OUT} = 0.1\mu F$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise specified.) (Note 4)


LOAD REGULATION
($V_{OUT} = 5V$)




DROPOUT VOLTAGE vs. OUTPUT CURRENT
($V_{OUT} = 2.5V$)




DROPOUT VOLTAGE vs. OUTPUT CURRENT
($V_{OUT} = 5V$)




POWER-SUPPLY REJECTION RATIO
vs. FREQUENCY ($V_{OUT} = 2.5V$)




POWER-SUPPLY REJECTION RATIO
vs. FREQUENCY ($V_{OUT} = 5V$)




SUPPLY CURRENT vs. INPUT VOLTAGE
($V_{OUT} = 2.5V$)




SUPPLY CURRENT vs. INPUT VOLTAGE
($V_{OUT} = 5V$)



0.1Hz TO 10Hz OUTPUT NOISE
($V_{OUT} = 2.5V$)



0.1Hz TO 10Hz OUTPUT NOISE
($V_{OUT} = 5V$)









Ultra-High-Precision SOT23 Series Voltage Reference

MAX6033

Typical Operating Characteristics (continued)







($V_{IN} = 5V$, $C_{OUT} = 0.1\mu F$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise specified.) (Note 4)



Ultra-High-Precision SOT23 Series Voltage Reference

Typical Operating Characteristics (continued)

($V_{IN} = 5V$, $C_{OUT} = 0.1\mu F$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise specified.) (Note 4)



Note 4: Many of the MAX6033 Typical Operating Characteristics are similar. The extremes of these characteristics are found in the MAX6033 (2.5V output) and the MAX6033 (5V output). The Typical Operating Characteristics of the remainder of the MAX6033 family typically lie between these two extremes and can be estimated based on their output voltages.

Ultra-High-Precision SOT23 Series Voltage Reference

MAX6033

Pin Description

PIN	NAME	FUNCTION
1, 3	I.C.	Internally Connected. Do not connect externally.
2	GND	Ground
4	IN	Positive Power-Supply Input
5	OUTF	Voltage Reference Force Output. Short OUTF to OUTS as close to the device as possible. Bypass OUTF with 0.1µF (min) capacitor to GND.
6	OUTS	Voltage Reference Sense

Applications Information

Bypassing/Load Capacitance

For the best line-transient performance, decouple the input with a 0.1µF ceramic capacitor as shown in the *Typical Operating Circuit*. Place the capacitor as close to IN as possible. When transient performance is less important, no capacitor is necessary.

The MAX6033 family requires a minimum output capacitance of 0.1µF for stability and is stable with capacitive loads (including the bypass capacitance) of up to 100µF. In applications where the load or the supply can experience step changes, a larger output capacitor reduces the amount of overshoot (undershoot) and improves the circuit's transient response. Place output capacitors as close to the device as possible.

Supply Current

The quiescent supply current of the MAX6033 series reference is typically 40µA and is virtually independent of the supply voltage. In the MAX6033 family, the load current is drawn from the input only when required, so supply current is not wasted and efficiency is maximized at all input voltages. This improved efficiency reduces power dissipation and extends battery life.

When the supply voltage is below the minimum-specified input voltage (as during turn-on), the devices can draw up to 150µA beyond the nominal supply current. The input voltage source must be capable of providing this current to ensure reliable turn-on.

Output-Voltage Hysteresis

Output voltage hysteresis is the change in the output voltage at TA = +25°C before and after the device is cycled over its entire operating temperature range. Hysteresis is caused by differential package stress appearing across the bandgap core transistors. The typical temperature hysteresis value is 150ppm.




Figure 1. Precision Current Source




Figure 2. 14-Bit High-Resolution DAC and Positive Reference from a Single 3V Supply

Turn-On Time

These devices typically turn on and settle to within 0.01% of their final value in >1µs. The turn-on time can increase up to 2ms with the device operating at the minimum dropout voltage and the maximum load.

Precision Current Source

Figure 1 shows a typical circuit providing a precision current source. The OUTF output provides the bias current for the bipolar transistor. OUTS senses the voltage across the resistor and adjusts the current sourced by OUTF accordingly.

High-Resolution DAC and Reference from Single Supply

Figure 2 shows a typical circuit providing both the power supply and reference for a high-resolution DAC. A MAX6033 with 2.5V output provides the reference voltage for the DAC.

Ultra-High-Precision SOT23 Series Voltage Reference

SOT23 Package Top Marks

PART	TOP MARK
MAX6033AAUT25	ABDF
MAX6033AAUT30	ABDG
MAX6033AAUT41	ABDH
MAX6033AAUT50	ABDI
MAX6033BAUT25	AAXL
MAX6033BAUT30	AAXM
MAX6033BAUT41	AAXN
MAX6033BAUT50	AAXO
MAX6033CAUT25	AAXH
MAX6033CAUT30	AAXI
MAX6033CAUT41	AAXJ
MAX6033CAUT50	AAXK

Chip Information


TRANSISTOR COUNT: 656

PROCESS: BiCMOS

Ultra-High-Precision SOT23 Series Voltage Reference

Package Information

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to www.maxim-ic.com/packages.)



MAX6033

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600 11