


[Home](#) > [Products](#) > > [89HPES16T16](#) > [89HPES16T16ZABL](#)

You may also like...

## 89HPES16T16ZABL

**Category:**  
**Generic Part:** [89HPES16T16](#)  
**Market Group:** SSP  
**Description:** PCIE 64-LANE 16 PORT SWIT



### Parameters

Speed	NA
Temperature	C
Voltage	1.0 V
Status	Active
Sample	Yes
Minimum Order Quantity	1
Factory Order Increment	1

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Application Note	AN-531, PCIe System Interconnect Software Architecture	155 KB	03/19/2007
	AN-571, PCIe System Interconnect SW Architecture for x86-based Systems	187 KB	05/22/2007
	AN-572, Upstream Port Redundancy & Failover for System Interconnect Switches	177 KB	05/24/2007

### Package

Package	FCBGA 1156 (BL1156)
Description	FLIP CHIP BGA 35 X 35 MM X 1.0MM PITCH
Status	Active
Class	PLASTIC
Category	<a href="#">Standard</a>
Pb (Lead) Free	<a href="#">No</a>
Mark	BL
Package Type	FCBGA
Lead Count	1156
Length	35.0 mm
Width	35.0 mm
Thickness	2.82 mm
Pitch	1.0 mm
Tube / Tray	TRAY
Quantity per Tube/Tray	24
Quantity per Reel	N/A
Moisture Sensitivity Level (MSL)	4
Moisture Exposure Floor Life	72 hrs@<30C/60%RH
Peak Reflow Temperature	225Å °C
Rebake Conditions	48hrs@125C
Related Package Documents	<a href="#">view documents</a>