

Datasheet for 76650-0053

General Information

Part Number: 76650-0053

Manufacturer: Molex / Waldom

Title: Deluxe Solderless Term Kit

Insulated Ring, Spade, Butt Splice, Closed-End Solderless Terminal .187" and .250 "

Description: Fully Insulated Female Quick Disconnect with Universal Crimp tool

Product Family: Terminals

Certificates: (Molex Parts within this kit) - EU RoHS Compliant

Country of Origin: Kit assembled in U.S.A.

Specifications

Design

Configuration: (Wire-to-Wire) and (Wire-to-Board) / Solderless Terminals

Connector Type: Solderless Terminals

Tab Sizes:.187" and .250"Stud Sizes:5-6 (M3-3.5)Insulation:Nylon and PVC

Wire size: (22-18), (16-14) and (12-10) AWG

Product Highlights

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade. Flags are a type of product that are used when there is a space constraint, and a regular straight Quick Disconnect is too large.

Piggyback Quick Disconnects can be used when multiple connections (also called piggyback) are required and there are a limited number of male tabs. The piggyback actually allows another QD to be connected to its tab and then the piggyback is connected to a tab.

Spades have the open tongue end used for rapid insertion on the mounting screw. The spade is usually used on free standing studs.

The Snap plug is a round bullet-like terminal that plugs or "snaps" into the female receptacle. Snaps are used in a variety of applications where a "quick disconnect" connection is needed, but there is not enough space for a normal QD coupler. Like a coupler set, the male and female pieces can be connected and disconnected many times.

Closed-end connectors are used in a variety of situations to "pigtail" or tie together 2 or more wires.

Butt Splices allow two stripped wires to be inserted into each end and "butt" in the center, with the crimp securing both wires together.

The Step Down Butt Splice is the perfect solution when 2 wires need to be inserted in one end of a splice and a single wire in the other end.



Datasheet for 76650-0053

Features and Benefits

- Color-coded insulator allows easy identification of terminal size and wire gauge.
- The Step Down Butt Splice is the perfect solution when 2 wires need to be spliced to a single wire
- Avikrimp provides a metal insulation support sleeve for superior strain relief
- The color-coded Nylon insulating sleeve extends beyond the metal support sleeve
- Terminal's funnel entrance is designed for increased crimping rates by speeding wire delivery into the crimp section and eliminating wire strand fold back.
- A wire stop stamped into the crimp barrel prevents insertion of over-stripped wires.

Applications

- MRO (Maintenance Repair and Operations)
- Consumer applications
- Power applications
- Motor applications
- Powertrains
- Transportation
- Construction / Mining
- Energy / Power
- Production Equipment
- Instrumentation
- Environmental Equipment and Controls
- Blower Motors

Bill of Materials for Part No. 76650-0053

Molex Part No.	Country	Description	Quantity in Kit
WICHER FAIT ING.	of Origin	Description	Νit
19002-0001	USA	Fully Insulated Female Quick Disconnect Stnd. Flare Tab, 22-18 AWG, .250", Red	25
19002-0005	USA	Fully Insulated Female Quick Disconnect Stnd. Flare Tab, 22-18 AWG, .187", Red	25
19002-0024	USA	Fully Insulated Female Quick Disconnect Stnd. Flare Tab, 22-18 AWG, .250", Blue	25
19002-0028	USA	Fully Insulated Female Quick Disconnect Stnd. Flare Tab, 22-18 AWG, .187", Blue	25
19003-0001	USA	Fully Insulated Female Quick Disconnect Stnd. Flare Tab, 22-18 AWG, .250", Pink	25
19003-0011	USA	Fully Insulated Female Quick Disconnect, 22-18 AWG, .187", Pink	25
19003-0040	USA	Fully Insulated Female Quick Disconnect Stnd. Flare Tab, 22-18 AWG, .250", Light Blue	25
19006-0001	USA	Fully Insulated Female Quick Disconnect Flag Terminal, 22-18 AWG, .250", Red	25
19006-0005	USA	Fully Insulated Female Quick Disconnect Flag Tab, 22-18 AWG, .187", Red	25
19006-0011	USA	Fully Insulated Female Quick Disconnect Flag Tab, 22-18 AWG, .250", Blue	25
19007-0001	USA	Fully Insulated Female Quick Disconnect Flag Terminal, 22- 18 AWG, .250", Pink	25
19007-0021	USA	Fully Insulated Female Quick Disconnect Flag Stnd. Flare Tab, 16-14 AWG, .250", Light Blue	25
19007-0029	USA	Fully Insulated Female Quick Disconnect Flag Stnd. Flare Tab, 16-14 AWG, .187", Light Blue	25

For additional Molex / Waldom Design and Solution kits please go to www.molexkits.com



1

Datasheet for 76650-0053

Bill of Materials for Part No. 76650-0053 continued Quantity in Country Molex Part No. of Origin Description Kit Fully Insulated Female Quick Disconnect Flag Terminal, 12-19007-0040 USA 10 AWG, .250", Yellow 25 Insulated Female Quick Disconnect Pig Back Stnd. Flare Tab, 19013-0025 Taiwan 22-18 AWG, .250", Pink 25 Insulated Female Quick Disconnect Nylon Tab, 22-18 AWG, 19019-0001 USA .110", Dark Pink 25 Insulated Female Quick Disconnect Terminal, 22-18 AWG, 19019-0006 USA .187", Dark Pink 25 Insulated Female Quick Disconnect Nylon Tab, 16-14 AWG, 19019-0031 USA .250", Light Blue 25 Insulated Female Quick Disconnect Terminal, 12-10 AWG, 19606-0002 USA .250", Yellow 25 19154-0004 USA PVC Ins. Butt Splice Connector, 22-18 AWG, Dark Pink 25 India Ins. Step-down Butt Connector, 22-14 AWG, Blue 19154-0022 25 USA Nylon Ins. Closed-end Connector, 22-12 AWG, Clear 19160-0009 25 Ins. Spade Tongue Terminal, 16-14 AWG, 5-6 (M3-3.5) stud USA 19198-0016 size, Light Blue 25 Ins. Spade Tongue Terminal, 22-18 AWG, 5-6 (M3-3.5) stud 19198-0070 USA size, Dark Pink 25 Molex Universal Crimp Tool-Bolt Cutter/Wire Stripper/Wire

Recommended Molex Tool(s) for Part No. 76650-0053*

Country

USA

19294-0003

	Country	
Molex Part No.	of Origin	Description
64001-0100 *	USA	Hand Crimp Tool (RHT-1990)
64001-0200 *	USA	Hand Crimp Tool (RHT-1991)
64001-0300 *	USA	Hand Crimp Tool (RHT-1993)
64001-0400 *	USA	Hand Crimp Tool (RHT-1994)
64001-0700 *	USA	Hand Crimp Tool (RHT-5757-CC)
64001-0800 *	USA	Hand Crimp Tool (RHT-5760)
64001-0900 *	USA	Hand Crimp Tool (RHT-7050)
64001-1000 *	USA	Hand Crimp Tool (RHT-5758-CC)
64001-1100 *	USA	Hand Crimp Tool (RHT-5762)
64001-1200 *	USA	Hand Crimp Tool (RHT-2050)
64001-1400 *	USA	Hand Crimp Tool (RHT-2100)
64001-1700 *	USA	Hand Crimp Tool (RHT-5757)
64001-2000 *	USA	Hand Crimp Tool (RHT-5758)
64001-2800 *	USA	Hand Crimp Tool T0102 Series
64001-4100 *	USA	Hand Crimp Tool (RHT-FIFG)
64001-4300 *	USA	Hand Crimp Tool (RHT-AFIFG)

Cutter, 22-10 AWG, Blue handles

^{*}Tool(s) not included in kit. Tool(s) ordered separately.