Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP24V28-2U

BP24V28-2U - External Battery Pack for UPS System



Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 24VDC external battery connector
- Simple installation; 2U rackmount, tower and stack adaptable
- 2-year warranty

Description

BP24V28-2U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems - OMNIVS1500XL, OMNIVSINT1500XL, SU750XL, SU750RTXL2U, SU1000XLa, SU1000RTXL2Ua, SUINT1000RTXL2Ua, SMART750RMXL2U, and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

• Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP24V28-2U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- $\bullet \ \, \text{Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems} \\$
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty
- NOTE: LIMIT OF 1 BP24V28-2U PER UPS, SEE BP24V70-3U FOR MULTI-PACK COMPATIBILITY

Specifications

BATTERY	
DC system voltage (VDC)	24

Connects to UPS via	Attached cable with red/black 75 amp male DC connector			
Typical battery lifespan	4-6 years typical (North America)			
PHYSICAL				
Shipping weight (lbs)	68			
Shipping weight (kg)	30.8			
Unit Dimensions (HWD/in)	3.5 x 17.5 x 14			
Unit Dimensions (HWD/cm)	8.9 x 44.5 x 35.6			
Shipping Dimensions (HWD/in)	6.75 x 23.5 x 18.25			
Shipping Dimensions (HWD/cm)	17.1 x 59.7 x 46.4			
Unit weight (lbs)	56.5			
Unit weight (kg)	25.6			
Material of construction	Steel			
Form factors supported	2U rack/tower			
CERTIFICATIONS				
Certifications	CE			
WARRANTY				
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty			
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available			

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Tower Stands	2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	-
Extended Warranties	WEXT3-BP24V	3-Year Extended Warranty - For All 24V Battery Packs	-
Extended Warranties	WEXT5-BP24V	5-Year Extended Warranty - For All 24V Battery Packs	-
Rackmount/Wallmount Kits	2POSTRMKITWM	Enables 2-Post Rackmount or Wallmount Installation of Select Rackmount UPS Systems	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3015.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.