



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: LS600

Line Conditioner - Automatic voltage regulation with surge protection

Highlights

- Automatically adjusts low voltage
- 600 watts continuous
- 2 NEMA 5-15 R outlets
- \$10,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite's LS600 automatic voltage regulation system offers complete protection from brownouts and transient surges for computers, printers, fax machines and more. Transformer-based voltage correction circuits maintain usable 120V nominal AC output during brownouts as low as 87V. Network grade equipment protection offers AC surge and noise suppression. Supports loads up to 600 watts. Includes 2 NEMA5-15R outlets, 6-ft. line cord and 1 LED that displays site power availability. \$10,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

Applications

- Maintains usable output voltage during severe brownouts for printers, fax machines, computers, audio/video equipment, CAD/CAM/CAE workstations, network nodes, file servers, phone systems, point-of-sale terminals, and other applications requiring steady input power.

Package Includes

- LS600 Line Conditioner
- Mounting hardware
- Instruction manual

Features

- Maintains usable 120V nominal output during brownouts as low as 87V
- 600 watts output power rating supports 120V loads up to 5 amps
- Network grade surge suppression
- Complete EMI/RFI noise filtering
- 3 diagnostic LEDs indicate input voltage status and surge suppression status
- 2 protected NEMA5-15R outlets
- 6-ft. AC power cord with standard NEMA5-15P input plug
- 2 year manufacturer's product warranty
- \$10,000 Ultimate Lifetime [connected equipment insurance](#) (USA & Canada Only)

Specifications

OUTPUT	
Output VA	600
Output nominal voltage	120v / 60Hz
Outlet quantity / type	2 NEMA5-15R
INPUT	

Input cord length (ft.)	8
Input cord length (m)	1.83
LEDS ALARMS & SWITCHES	
Front panel LEDs	1 LED indicates line power is present
SURGE / NOISE SUPPRESSION	
UPS AC suppression joule rating	240 joules
EMI / RFI AC noise suppression	20 dB
PHYSICAL	
Shipping weight (lbs)	5.00
Shipping weight (kg)	2.27
Unit Dimensions (HWD/in)	5.75 x 4.25 x 5.25
Material of construction	Plastic
Form factors supported	Small Tower
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=206.

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.