



# Model #: PS-615-HG

## Power Strip - With Hospital-Grade Plug & Receptacles



## **Highlights**

- Versatile power distribution strip
- 6 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- 15A resettable circuit breaker

## **Description**

Tripp Lite's PS-615-HG Power Strip offers 15A capacity AC power distribution in a rugged all-metal outlet strip for 120V applications. Features 6 hospital grade-receptacles, 15-ft. AC power cord and built-in resettable circuit breaker. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

#### Applications

- · AC power distribution with hospital-grade receptacles and plug where durability and reliability are required.
- Not for use where NEC requires hospital-grade receptacles.

#### Package Includes

- PS-615-HG Power Strip
- User manual with warranty information

#### **Features**

- Rugged all-metal housing withstands years of use without breakage
- 6 x NEMA 5-15R-HG hospital-grade output receptacles
- 15-ft. AC cord with integrated, molded NEMA 5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges.
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)

## **Specifications**

Model Type   NOT For Patient Areas    OUTPUT    Frequency compatibility   50 / 60 Hz    Output volt amp capacity (amps)    Overload protection   15A circuit breaker    Outlet quantity / type   6 NEMA 5-15R-HG    Outlet orientation   Single row of 6    INPUT    Recommended Electrical   15A 120V    Service   Input connection type   NEMA 5-15P-HG    Input cord length (ft.)   15    Input cord length (m)   4-572    Voltage compatibility (VAC)   120    LEDS ALARMS & SWITCHES    Switches   No power switch    PHYSICAL    Unit Dimensions (HWD/in)   1.5 x 13.75 x 2.5    Unit Dimensions (HWD/cm)   3.8 x 34.9 x 6.4    Material of construction   Metal    Integrated keyhole mounting   Keyhole mounting tabs and flanges enable mounting to a variety of surfaces    Receptacle Color   White    AC line cord color   White	
Frequency compatibility 50 / 60 Hz  Output volt amp capacity (amps) 15  Overload protection 15A circuit breaker  Outlet quantity / type 6 NEMA 5-15R-HG  Outlet orientation Single row of 6  INPUT  Recommended Electrical 15A 120V  Service 15A 120V  Input connection type NEMA 5-15P-HG  Input cord length (ft.) 15  Input cord length (m) 4.572  Voltage compatibility (VAC) 120  LEDS ALARMS & SWITCHES  Switches No power switch  PHYSICAL  Unit Dimensions (HWD/in) 1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm) 3.8 x 34.9 x 6.4  Material of construction Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces Receptacle Color White	
Output volt amp capacity (amps)  Overload protection  15A circuit breaker  Outlet quantity / type  6 NEMA 5-15R-HG  Outlet orientation  Single row of 6  INPUT  Recommended Electrical Service  15A 120V  Input connection type  NEMA 5-15P-HG  Input cord length (ft.)  15  Input cord length (m)  4.572  Voltage compatibility (VAC)  LEDS ALARMS & SWITCHES  Switches  No power switch  PHYSICAL  Unit Dimensions (HWD/in)  1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm)  Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color  White	
Overload protection 15A circuit breaker  Outlet quantity / type 6 NEMA 5-15R-HG  Outlet orientation Single row of 6  INPUT  Recommended Electrical Service 15A 120V  Input connection type NEMA 5-15P-HG  Input cord length (ft.) 15  Input cord length (m) 4.572  Voltage compatibility (VAC) 120  LEDS ALARMS & SWITCHES  Switches No power switch  PHYSICAL  Unit Dimensions (HWD/in) 1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm) 3.8 x 34.9 x 6.4  Material of construction Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color White	
Outlet quantity / type 6 NEMA 5-15R-HG  Outlet orientation Single row of 6  INPUT  Recommended Electrical 15A 120V Service Input connection type NEMA 5-15P-HG  Input cord length (ft.) 15  Input cord length (m) 4.572  Voltage compatibility (VAC) 120  LEDS ALARMS & SWITCHES  Switches No power switch  PHYSICAL  Unit Dimensions (HWD/In) 1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm) 3.8 x 34.9 x 6.4  Material of construction Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color White	
Outlet orientation  INPUT  Recommended Electrical	
INPUT  Recommended Electrical Service  Input connection type  NEMA 5-15P-HG  Input cord length (ft.)  Input cord length (m)  4.572  Voltage compatibility (VAC)  LEDS ALARMS & SWITCHES  Switches  No power switch  PHYSICAL  Unit Dimensions (HWD/in)  1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm)  Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color  White	
Recommended Electrical Service  Input connection type  NEMA 5-15P-HG  Input cord length (ft.)  Input cord length (m)  4.572  Voltage compatibility (VAC)  LEDS ALARMS & SWITCHES  Switches  No power switch  PHYSICAL  Unit Dimensions (HWD/in)  1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm)  Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color  White	
Input connection type	
Input cord length (ft.)  Input cord length (m)  4.572  Voltage compatibility (VAC)  LEDS ALARMS & SWITCHES  Switches  No power switch  PHYSICAL  Unit Dimensions (HWD/in)  1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm)  3.8 x 34.9 x 6.4  Material of construction  Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color  White	
Input cord length (m)  4.572  Voltage compatibility (VAC)  LEDS ALARMS & SWITCHES  Switches  No power switch  PHYSICAL  Unit Dimensions (HWD/in)  1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm)  3.8 x 34.9 x 6.4  Material of construction  Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces  Receptacle Color  White	
Voltage compatibility (VAC)  LEDS ALARMS & SWITCHES  Switches  PHYSICAL  Unit Dimensions (HWD/in)  1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm)  3.8 x 34.9 x 6.4  Material of construction  Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces  Receptacle Color  White	
Switches   No power switch	
Switches     No power switch       PHYSICAL       Unit Dimensions (HWD/in)     1.5 x 13.75 x 2.5       Unit Dimensions (HWD/cm)     3.8 x 34.9 x 6.4       Material of construction     Metal       Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs       Receptacle Color     White	
PHYSICAL  Unit Dimensions (HWD/in) 1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm) 3.8 x 34.9 x 6.4  Material of construction Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color White	
Unit Dimensions (HWD/in)  1.5 x 13.75 x 2.5  Unit Dimensions (HWD/cm)  3.8 x 34.9 x 6.4  Material of construction  Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces  Receptacle Color  White	
Unit Dimensions (HWD/cm)  3.8 x 34.9 x 6.4  Material of construction  Metal  Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color  White	
Material of construction         Metal           Integrated keyhole mounting tabs         Keyhole mounting tabs and flanges enable mounting to a variety of surfaces           Receptacle Color         White	
Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs  Receptacle Color  White	
Receptacle Color White	
AC line cord color White	
CERTIFICATIONS	
UL1363 (Power Tap)  UL1363 (Series Number: AGIB12015SL)	
cUL / CSA (Canada) cUL (Series Number: AGIB12015SL)	
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)  Lifetime limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=205.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.