

Tripp Lite 1111 West 35th Street Chicago, IL 60609 USA Telephone: +(773) 869 1234

E-mail: saleshelp@tripplite.com

Model #: SS7415-15

16 outlet, 15-ft cord, 450 joule Power Strip with Surge Suppression

Highlights

- 16 outlets
- 15-ft. cord
- 48-in. length
- 450-joule rating



Description

The SS7415-15 4-ft. power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 16 NEMA 5-15R output receptacles with 2.717-in. center-to-center spacing, 15-ft. AC line cord and adjustable mounting clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 450 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray housing with black output receptacles.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 16 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: 4-ft. corded vertical/raceway power distribution strip

SURGE SUPPRESSION: 450 joules

Applications

. Offers outlet power distribution with surge suppression for multiple loads in equipment racks, computer rooms, workbenches and raceways in a variety of internetworking, telecommunications, audio/video and live sound applications.

Package Includes

- SS7415-15 Power Strip/Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual

Specifications

OVERVIEW	
Intended Application	Computer Networking, Industrial/Factory Floor
OUTPUT	

Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Output volt amp capacity (amps)	15	
Outlet quantity / type	16 NEMA 5-15R	
Outlet spacing	2.717-in. center-to-center spacing	
INPUT		
Recommended Electrical Service	120V	
Input connection type	NEMA 5-15P	
Input cord length (ft.)	15	
Voltage compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Switches	Lighted 2-position power switch controls power to all outlets	
Locking switch cover	Transparent locking switch cover	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	450	
UL1499 let through rating	500V UL verified	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Unit Dimensions (HWD/in)	48 x 1.5 x 1.5	
Mounting accessories included	Set of adjustable mounting clamps	
Receptacle Color	Black	
AC line cord color	Black	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd EDITION	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=1948.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.