



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SPIKECUBE

### 1-outlet, Direct plug-in, 540 joule Surge Suppressor

#### Highlights

- 1 outlet/direct plug-in
- 540 joule rating



#### Description

The SPIKECUBE Surge Suppressor from Tripp Lite is a direct plug-in suppressor providing protection on one AC outlet. Its small size makes it ideal for protecting laptop computers, projectors and other portable electronics. A "Protected" LED illuminates to indicate that adequate surge suppression is available. The unit has 540 joules of surge energy absorption. Lifetime warranty with \$5,000 Ultimate Lifetime [connected equipment insurance](#) (USA & Canada Only).

#### Applications

- Ideal for laptop computers, video projectors, office machines, and appliances

#### Package Includes

- SPIKECUBE Surge Suppressor
- Warranty and instruction information

#### Features

- 1 outlet; direct plug-in
- Surge energy absorption: 540 joules; 6,500 amps
- \$5,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Specifications

OVERVIEW	
Intended Application	Home/Office, Travel
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output watts	1800
Output volt amp capacity (amps)	15

Outlet quantity / type	1 NEMA 5-15R
<b>INPUT</b>	
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P input plug
Input cord length details	Direct Plug-In
Voltage compatibility (VAC)	120
<b>LEDS ALARMS &amp; SWITCHES</b>	
Diagnostic LEDs	Built-in "Protected" status indicator
<b>SURGE / NOISE SUPPRESSION</b>	
AC suppression joule rating	540
AC suppression response time	< 1 ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
Clamping voltage (RMS)	150
UL1499 let through rating	500V - UL Verified
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Shipping weight (lbs)	.17
Unit Dimensions (HWD/in)	2.05 x 1.94 x 1.50
Shipping Dimensions (HWD/in)	5.05 x 3.55 x 2.50
Unit weight (lbs)	.125
Material of construction	Plastic
Style	Direct plug-in
Form factors supported	Direct plug in suppressor supports wall-mounting directly into AC receptacle
<b>SPECIAL FEATURES</b>	
Appearance	Ultra-compact portable direct plug-in protector in an attractive, grey lightweight enclosure
<b>CERTIFICATIONS</b>	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
Approvals	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty

**Connected Equipment  
Insurance (U.S., Canada &  
Puerto Rico)**

\$5,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=120](http://www.tripplite.com/en/products/model.cfm?txtModelID=120).

---

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.