

## Model #: DG206

1050-Joule Commercial-Grade Surge Suppressor with illuminated On/Off switch, diagnostic LEDs, and a heavy-duty metal housing with keyhole slots



## **Highlights**

- 6 outlets/6 ft. cord
- 1050 joule rating

## **Description**

The Waber-by-Tripp Lite DG206 Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 1050 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded metal power distribution strip with lighted power switch

SUPPRESSION - 1050 joules AC suppression

#### Applications

 Offers multiple outlet power distribution and surge suppression in workbench, wallmount or floor mount applications. Ideal protection for home appliances, entertainment centers, industrial equipment and other electronic loads.

### Package Includes

- DG206 Power Strip
- Warranty information
- Instruction manual

#### **Features**

- · Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tabs support permanent installation on a wide variety of surfaces
- UL1449 (USA/400V rating), UL1363 (USA), cUL (Canada)

- 15 amp power handling capacity
- 6 foot AC line cord
- Lifetime warranty

# **Specifications**

OVERVIEW	OVERVIEW		
Intended Application	Industrial/Factory Floor		
OUTPUT	OUTPUT		
Frequency compatibility	50 / 60 Hz		
Output watts	1800		
Output volt amp capacity (amps)	15		
Outlet quantity / type	6 NEMA 5-15R		
INPUT			
Recommended Electrical Service	120V (110-125V)		
Input connection type	NEMA 5-15P input plug		
Input cord length (ft.)	6		
Input cord length (m)	1.8		
Input cord gauge, type	14 gauge, SJT		
Voltage compatibility (VAC)	120		
LEDS ALARMS & SWITCHES			
Switches	Lighted two position power switch controls power to all outlets		
Diagnostic LEDs	Protection present (green)		
SURGE / NOISE SUPPRESSION			
AC suppression joule rating	1050		
AC suppression response time	< 1 ns		
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression		
UL1499 let through rating	400V - UL Verified		
Immunity	Conforms to IEE 587 / ANSI C62.41		
DATALINE SURGE SUPPRESSION			
Telephone/DSL Protection	No		
Cable (Coax) Protection	No		
Network (Ethernet) Protection	No		
PHYSICAL			
Shipping weight (lbs)	10		
Shipping weight (kg)	4.5		
Unit Dimensions (HWD/in)	1.25 x 2.5 x 12.25		

Unit Dimensions (HWD/cm)	3.175 x 6.35 x 31.12
Shipping Dimensions (HWD/in)	2.25 x 15 x 6
Shipping Dimensions (HWD/cm)	5.7 x 38.1 x 15.24
Unit weight (lbs)	2.4
Unit weight (kg)	1.08
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
Receptacle Color	Gray
AC line cord color	Gray
Style	Strip
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=1969.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.