



# Model #: TLM606

#### **Protect It! Surge Suppressor**



### **Highlights**

- 6 outlets / 6 ft. cord
- 280 joule rating
- \$5,000 Ultimate Lifetime Insurance (USA & Canada only)

## **Description**

Tripp Lite's TLM606 surge suppressor offers complete AC surge suppression for comprehensive protection of personal computers, home stereos, televisions, VCRs, DVD players, power tools and other electrical and electronic equipment. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLM606 offers 6 total outlets, a 6 foot power cord and diagnostic LED to warn of suppressor damage. AC surge suppression rated at 280 joules shields equipment from surges and line noise. Rugged metal housing offers convenient protection of desktop computer equipment and accessories. Lifetime warranty with \$5,000 Ultimate Lifetime Insurance (USA & Canada Only).

PLUG/OUTLETS: Input - 6 ft. AC line cord with NEMA 5-15P plug/Output - 6 NEMA 5-15R outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT: Metal strip

SUPPRESSION: AC: 150V RMS Clamping/280 joules/330V UL1449

#### Applications

• Ideal for personal computers, TV/VCR/DVD, stereos, power tools and lamps/lighting

### Package Includes

- TLM606 surge suppressor
- Instruction manual and warranty information

#### **Features**

- 6 outlets
- 6 ft. cord
- Surge suppression rating: 280 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker protects against overload
- Diagnostic LED confirms suppressor "protection present" (green)
- Convenient keyhole slots allow secure mounting on wall or desk

- Can accommodate up to 1 transformers without blocking adjacent outlets
- Rugged metal case provides extra safety and durability
- Illuminated power switch
- \$5,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment
- Lifetime product warranty

# **Specifications**

| OVERVIEW                        |  |  |  |
|---------------------------------|--|--|--|
| Intended Application            | Home/Office  |  |  |
| OUTPUT                          | ОИТРИТ   |  |  |
| Frequency compatibility         | 50 / 60 Hz   |  |  |
| Output watts                    | 1800   |  |  |
| Output volt amp capacity (amps) | 15   |  |  |
| Overload protection             | 15A circuit breaker  |  |  |
| Outlet quantity / type          | 6 NEMA 5-15R   |  |  |
| Transformer accommodation       | Supports 1 large transformer without covering adjacent outlets                     |  |  |
| Outlet orientation              | Single row of outlets  |  |  |
| INPUT                           |  |  |  |
| Recommended Electrical Service  | 120V (110-125V)  |  |  |
| Input connection type           | NEMA 5-15P   |  |  |
| Input cord length (ft.)         | 6  |  |  |
| Input cord length (m)           | 1.8  |  |  |
| Input cord gauge, type          | 14 gauge, SJT  |  |  |
| Voltage compatibility (VAC)     | 120  |  |  |
| LEDS ALARMS & SWITCHES          |  |  |  |
| Switches                        | 2 position on/off power switch   |  |  |
| Diagnostic LEDs                 | Built-in LED confirms suppressor "protection present" (green) status               |  |  |
| SURGE / NOISE SUPPRESSION       |  |  |  |
| AC suppression joule rating     | 280  |  |  |
| AC suppression response time    | < 1 ns   |  |  |
| Protection modes                | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |  |  |
| Clamping voltage (RMS)          | 150V   |  |  |
| UL1499 let through rating       | 330V - UL Verified   |  |  |
| EMI / RFI filtering             | Up to 20dB   |  |  |
| DATALINE SURGE SUPPRESSION      |  |  |  |
| Telephone/DSL Protection        | No   |  |  |
| Cable (Coax) Protection         | No   |  |  |

| Network (Ethernet) Protection                                    | No   |
|--|--|
| PHYSICAL   |  |
| Shipping weight (lbs)  | 1.6  |
| Shipping weight (kg)   | .7   |
| Unit Dimensions (HWD/in)   | 1.5 x 12.5 x 2.5   |
| Unit Dimensions (HWD/cm)   | 3.8 x 31.8 x 6.3   |
| Shipping Dimensions<br>(HWD/in)                                  | 1.75 x 15.5 x 4.5  |
| Shipping Dimensions (HWD/cm)                                     | 4.4 x 39.4 x 11.4  |
| Unit weight (lbs)  | 1.4  |
| Unit weight (kg)   | .6   |
| Material of construction   | Metal  |
| Integrated keyhole mounting tabs                                 | Keyhole slots enable mounting to a variety of surfaces             |
| Receptacle Color   | Light Gray   |
| AC line cord color   | Light Gray   |
| Style  | Strip  |
| Form factors supported   | Supports floor / wall / desktop placement                          |
| CERTIFICATIONS   |  |
| Additional International Approvals                               | Complies with RoHS (Restriction of Hazardous Substances Directive) |
| UL1449 3rd Edition (AC<br>Suppression)                           | UL1449   |
| UL1363 (Power Tap)   | UL1363   |
| cUL / CSA (Canada)   | cUL  |
| Approvals  | Exceeds IEEE 587 category A&B specifications                       |
| WARRANTY   |  |
| Product Warranty Period<br>(U.S., Canada & Puerto Rico)          | Lifetime limited warranty  |
| Connected Equipment<br>Insurance (U.S., Canada &<br>Puerto Rico) | \$5,000 Ultimate Lifetime Insurance                                |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3306.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.