



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TRAVELERC6

**2 (C6) 3-prong connectors, in-line surge suppressor with 1 in/2 out tel/modem surge protection**

### Highlights



- 120V / 240V compatible
- 306 joule rating at 120V;  
820 joule rating at 240V
- Two 3-prong (C6) connectors
- 1 in/2 out tel/modem surge protection
- In-line design
- \$100,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

### Description

Tripp Lite's Traveler In-Line surge suppressor features a 306 joule rating to handle even the strongest surges (820 joule rating at 240V AC). In-line design, over current protection and 120/240V compatibility make this surge suppressor ideal for notebook computers and PDAs. Integrated phone line protection allows you to safeguard tel/modem and AC connections with a single unit. "Protected" and "Over Current" LEDs let you instantly know whether your wall jacks have potentially damaging signals. Lifetime warranty with \$100,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

CONNECTORS: Interfaces with C6 (3 conductor laptop type) cabling

ELECTRICAL: 120V and 240V AC, 50/60Hz

FORMAT: In-line design that puts surge protection between your notebook computer or PDAs' power adapter and the power cord leading to the wall outlet

SUPPRESSION: AC: 150V RMS Clamping/306 joules (120V AC) or 820 joules (240V AC)/900V UL1449 3rd Edition let-through rating

#### Applications

- Ideal for notebook computers, PDAs or other electronics requiring AC and tel/modem safeguarding

#### Package Includes

- TRAVELERC6 surge suppressor
- 6-ft. phone cord
- Instruction manual with warranty information

### Features

- In-line design places AC line surge protection between your notebook computer or PDAs' power adapter and the power cord leading to the wall outlet
- 120/240V compatibility operates on voltage worldwide, automatically switching between 120V or 240V AC power
- Surge suppression rating: 306 joules (100-120V)/820 joules (220-240V)
- Includes two 3-prong (C6) connectors
- Built-in LEDs confirm suppressor "protection present" (green) and "overcurrent detection" (red) status
- Tel/modem RJ11 jacks provide complete surge protection for modem, fax or telephone connections. Built-in splitter (1 in/2 out) allows

simultaneous connection and protection of two devices on a single line

- Single small push-button switch activates overcurrent detection circuit
- \$100,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only) covers connected equipment
- Lifetime product warranty

## Specifications

OVERVIEW	
Intended Application	Home/Office, Travel
OUTPUT	
Frequency compatibility	50 / 60 Hz
Outlet quantity / type	2 (C6) 3-prong connectors
INPUT	
Recommended Electrical Service	120V (110-125V), 230V (220-250V)
Input connection type	Two 3-prong (C6) connectors
Input cord length details	In-line
Voltage compatibility (VAC)	120; 230
LEDS ALARMS & SWITCHES	
Switches	Single small push-button switch activates over-current detection circuit
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "over-current detection" (red) status
SURGE / NOISE SUPPRESSION	
AC suppression joule rating	306
AC suppression joule rating details	820 joule rating at 240V
AC suppression response time	< 1 ns
Clamping voltage (RMS)	150
UL1499 let through rating	900V
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	

<b>Unit Dimensions (HWD/in)</b>	1.75 x 4.25 x 1
<b>Unit Dimensions (HWD/cm)</b>	4.4 x 10.8 x 2.5
<b>Shipping Dimensions (HWD/in)</b>	9 x 7 x 1.2
<b>Shipping Dimensions (HWD/cm)</b>	22.9 x 17.8 x 3
<b>Unit weight (lbs)</b>	0.2
<b>Unit weight (kg)</b>	0.1
<b>Material of construction</b>	Plastic
<b>Style</b>	In-Line
<b>Form factors supported</b>	In-line
<b>SPECIAL FEATURES</b>	
<b>Appearance</b>	Ultra-compact portable in-line protector in an attractive, all black lightweight enclosure
<b>Additional Information</b>	Phone line protection circuits includes a switch to activate over-current detection circuit able to detect digital phone lines that could potentially damage standard dialup modems. Simply connect the protector to an active phone jack and press the button. If RED LED illuminates, the jack wired for digital or other profile that may not be compatible with standard dialup modems
<b>CERTIFICATIONS</b>	
<b>UL1449 3rd Edition (AC Suppression)</b>	UL1449 3rd Edition
<b>UL497A (Communications)</b>	UL497A
<b>FCC Part 68 (Communications)</b>	FCC Part 68
<b>cUL / CSA (Canada)</b>	cUL
<b>Approvals</b>	UL1950
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	Lifetime limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$100,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2638](http://www.tripplite.com/en/products/model.cfm?txtModelID=2638).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.