



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: ISOTEL8ULTRA

**8-outlets, 12-ft cord, 3840 joule, RJ11 protection, All metal housing Isobar Surge Suppressor - Premium surge, spike and line noise protection**

### Highlights

- 8 outlets / 12-ft. cord
- 3840 joule rating
- All metal housing with LEDs
- Isolated filter banks
- Modem/fax surge protection
- \$50,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)



### Description

For more than 20 years, America's leading companies have trusted Tripp Lite's Isobar Premium surge and noise suppressors to protect sensitive computer, networking and telecom equipment. With more than 14 million satisfied customers, the Isobar remains the world's #1 selling premium surge suppressor. Loaded with a generous combination of high quality components, near indestructible all-metal case, unique noise filtration system and built-in single line phone suppression for modems, the Isobar/Isotel series offers the highest level of protection attainable in a multi-outlet strip. Robust surge suppression circuits with sine-wave tracking offer extreme levels of protection against the heaviest surge conditions exceeding IEEE 587 category A & B specifications and reducing 6,000V test surges to harmless levels under 35 volts. Isobar's unique protection system combines large toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors into exclusive isolated filter banks that remove EMI/RFI interference, even noise generated by other pieces of connected equipment. ISOTEL8ULTRA offers 8 outlets arranged in four filter banks to prevent system crashes, reboots and performance problems common as noisy system peripherals are powered off and on. Surge suppression rated at 3840 joules/92,000 amps offers network-grade protection. Widely spaced NEMA 5-15 outlets accommodate up to 4 large transformer plugs without blocking outlets. Pair of RJ11 jacks offer single phone line surge suppression for modems, fax machines and cordless phones. Diagnostic LEDs confirm power availability, line fault and protection status. Includes 12 foot AC line cord with space-saving angled input plug, keyhole mounting tabs and a set of 4 child safety covers. Lifetime warranty with \$50,000 Ultimate Lifetime [connected equipment insurance](#) (USA & Canada Only).

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 8 NEMA5-15R/12-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz (Requires NEMA 5-15R wall receptacle)

SUPPRESSION: AC: 140V RMS Clamping/3840 joules/92,000 amps PHONE: Single line protection starts at 260V

FORMAT: Corded all-metal strip with transformer spaced outlets

#### Applications

- Ideal for premium AC and phone line protection for personal computers with peripherals, network and CAD/CAM/CAE workstations, internetworking accessories, telecommunications systems, point of sale equipment, audio/video and home theater systems in any home, office or industrial application.

#### Package Includes

- ISOTEL8ULTRA Surge Suppressor
- RJ11 telephone cable
- Set of 4 outlet safety covers
- Instruction manual with warranty information

## Features

- Tripp Lite's ISOBAR/ISOTEL is the world's #1 selling premium suppressor series with more than 14 million satisfied customers and a safety-tested history of 20+ years
- Robust surge suppression with sine-wave tracking protects against the heaviest of surge conditions, exceeding IEEE category A&B specifications and reducing 6,000V test surges to harmless levels less than 35 volts
- Multi-component suppression circuits combine toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors into exclusive isolated filter banks that remove EMI/RFI interference, even noise from other pieces of connected equipment
- Single phone line surge suppression protects modems, fax machines and cordless phones (2 wire, single line, RJ11 jacks)
- 8 outlets arranged in four filter banks prevent system crashes, reboots and performance problems common as noisy peripherals are powered off and on
- Network grade surge suppression rated at 3840 joules/92,000 amps
- Widely spaced outlets accommodate up to 4 large transformer plugs without blocking outlets
- 3 LED indicators confirm suppressor operation and site wiring status, plus warning of suppressor or electrical fault conditions
- Lighted power switch confirms power on/off status
- 12 foot AC line cord with space-saving angled input plug
- Keyhole mounting tabs allow permanent installation
- Set of 4 outlet covers safely seal off unused outlets
- 120VAC, 50/60Hz electrical compatibility
- \$50,000 Ultimate Lifetime Insurance (USA & Canada Only)
- Lifetime product warranty
- UL1449 3rd Edition listed - surge suppression (330V let-through), UL1283 listed - EMI protection, UL1363 listed - power tap, UL497A listed - communications suppression, cUL approved to Canadian standards, Complies with part 68 - FCC rules

## Specifications

OVERVIEW	
Intended Application	Home/Office, Computer Networks
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output watts	1440
Output volt amp capacity (amps)	12
Outlet quantity / type	8 NEMA 5-15R
Transformer accommodation	Supports up to 4 large transformer plug accessories without covering remaining outlets
INPUT	
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P input plug
Input plug features	Space-saving right angle input plug
Input cord length (ft.)	12
Voltage compatibility (VAC)	120
LEDS ALARMS & SWITCHES	

<b>Switches</b>	Two position red illuminated on/off power switch
<b>Diagnostic LEDs</b>	PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)
<b>SURGE / NOISE SUPPRESSION</b>	
<b>AC suppression joule rating</b>	3840
<b>AC suppression response time</b>	NM = 0 ns. CM =
<b>Protection modes</b>	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
<b>Clamping voltage (RMS)</b>	140
<b>AC suppression surge current rating</b>	92,000 amps (36,000 NM / 56,000 CM)
<b>AC suppression components used</b>	Metal oxide varistors, toroidal balanced chokes, ferrite rod-core inductors and VHF capacitors.
<b>Safe thermal fusing</b>	Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences
<b>UL1499 let through rating</b>	330V - UL Verified
<b>IEEE587 Cat. A ringwave let through</b>	Less than 35 volts
<b>EMI / RFI filtering</b>	40-80 dB
<b>Isolated filter banks</b>	Unique isolated filter bank design offers additional filtering between each duplex pair of outlets on the strip to prevent electrical noise interference between connected loads. Includes 4 filter banks.
<b>Immunity</b>	Conforms to IEE 587 / ANSI C62.41
<b>DATALINE SURGE SUPPRESSION</b>	
<b>Telephone/DSL Protection Details</b>	1 line
<b>Cable (Coax) Protection</b>	No
<b>Network (Ethernet) Protection</b>	No
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	3.9
<b>Unit Dimensions (HWD/in)</b>	2.5 x 9 x 3.5
<b>Shipping Dimensions (HWD/in)</b>	11.5 x 7 x 3
<b>Unit weight (lbs)</b>	3.4
<b>Material of construction</b>	Metal
<b>Integrated keyhole mounting tabs</b>	Metal end caps are fitted with keyhole mounting tabs for wallmount installation
<b>Receptacle Color</b>	Black
<b>AC line cord color</b>	Gray
<b>Style</b>	Strip
<b>SPECIAL FEATURES</b>	

<b>Appearance</b>	Rugged all-metal corded strip format with high quality duplex receptacles
<b>Right-Angle Plug</b>	Yes
<b>CERTIFICATIONS</b>	
<b>UL1449 3rd Edition (AC Suppression)</b>	UL1449 3rd Edition
<b>UL1283 (EMI Filter)</b>	UL1283
<b>UL1363 (Power Tap)</b>	UL1363
<b>UL497A (Communications)</b>	UL497A
<b>FCC Part 68 (Communications)</b>	FCC Part 68
<b>cUL / CSA (Canada)</b>	cUL
<b>Industry Canada (Communications)</b>	Industry Canada
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	Lifetime limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$50,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=112](http://www.tripplite.com/en/products/model.cfm?txtModelID=112).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.