

# Model #: HT10DBS

# 10 outlet, 8ft cord, 3570 joule, All metal housing block, 3-line coaxial 1-line tel/modem 1-line network protection - Isobar Home/Business Theater Premium Surge Suppressor



# Highlights

- 10 outlets / 8-ft. cord
- 3570 joule rating
- Isolated Filter Banks / all-metal housing
- 3-line coaxial (gold) surge protection
- 1-line tel/modem and 1-line network (100BaseT, high-speed) surge protection
- \$500,000 Ultimate Lifetime Insurance (USA and Canada only)

# **Description**

Tripp Lite's HT10DBS Isobar Home/Business Theater Surge Suppressor provides premium protection--3570 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for medium-to-large home/business theater installations: high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more. Exclusive Isolated Filter Banks eliminate noise interference between components. 10 outlets (with transformer spacing and plug-in safety covers), 3-line coaxial protection, 1-line tel/modem protection and 1-line network (100BaseT, high-speed) protection safeguard an entire home/business theater system. \$500,000 Ultimate Lifetime Insurance coverage (USA and Canada only). Includes all-metal housing, color-coordinated outlet/plug labels, three diagnostic LEDs, 8-ft. cord with a right-angle plug, 6-ft. gold coax cable, 6-ft. phone cord and 6-ft. network cable.

#### Applications

• Perfect for medium-to-large home/business theater installations: high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more.

## Package Includes

- HT10DBS Home/Business Theater Surge Suppressor
- 6-ft. DSS cable
- 6-ft. phone cord
- 6-ft. network cable
- Instruction manual with warranty information

## **Features**

- 3570 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$500,000 Ultimate Lifetime Insurance (USA and Canada only) covers connected components against surge damage...for life!
- Isolated Filter Banks eliminate interference between connected components
- All-metal housing safely withstands the strongest surges
- 10 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely spaced outlets accommodate up to 6 transformers

- Four plug-in safety covers protect against accidental contact with unused outlets
- 3 sets of surge-protected Type F gold coaxial connectors (with included 6-ft. gold coax cable) safeguard components on cable, satellite and antenna line
- 1-line tel/modem and 1-line network (100BaseT, high-speed) surge protection (with included 6-ft. phone cord and 6-ft. network cable) safeguards personal video recorders (PVRs) on up to two lines simultaneously.
- 8-ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 3 diagnostic LEDs alert user to protection, line power and ground status
- Keyhole slots provide convenient wall or cabinet mounting
- Illuminated master switch provides one-touch power control over all components. Circuit breaker protects against dangerous system overload
- All-metal housing (black) stands up to the most demanding environments
- UL and cUL listed
- Lifetime product warranty
- Color-coordinated outlet/plug labels

# **Specifications**

OVERVIEW		
Intended Application	Audio/Video	
OUTPUT		
Frequency compatibility	50 / 60 Hz	
Output watts	1440	
Output volt amp capacity (amps)	12	
Outlet quantity / type	10 NEMA 5-15R	
Transformer accommodation	Accommodates 6 transformers	
INPUT		
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P	
Input plug features	Space-saving right-angle input plug	
Input cord length (ft.)	8	
Input cord length (m)	2.4	
Input cord gauge, type	14 gauge, SJT	
Voltage compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Switches	Combination AC circuit breaker and illuminated 2 position on/off power switch	
Diagnostic LEDs	Built-in LEDs confirm line power, protection and ground status	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	3570	
AC suppression response time	NM = instantaneous CM = < 1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS)	140V	

UL1499 let through rating	330V - UL verified	
EMI / RFI filtering	Up to 60 dB	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	Yes	
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	Yes	
Cable (Coax) Protection Details	3 line	
Network (Ethernet) Protection	Yes	
PHYSICAL		
Unit Dimensions (HWD/in)	14.25 x 2.25 x 3.5	
Unit Dimensions (HWD/cm)	36.2 x 2 x 5.7	
Unit weight (Ibs)	3.5	
Unit weight (kg)	1.6	
Material of construction	Metal	
Integrated keyhole mounting tabs	Keyhole mounting slots allow desk or wall mounting	
AC line cord color	Black	
Style	Strip	
SPECIAL FEATURES		
Right-Angle Plug	Yes	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449	
UL1363 (Power Tap)	UL1363	
UL497A (Communications)	UL497A	
FCC Part 68 (Communications)	FCC Part 68	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$500,000 Ultimate Lifetime Insurance	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModeIID=2813.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.