

Model #: TR-6FM

6 outlet, 6-ft cord, 3040 joules, Modem/Fax protection Surge Suppressor - State of the art protection for every application



Highlights

- 6 outlets/6 ft. cord
- 3040 joule rating
- Modem/fax surge protection
- \$50,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Description

The TR-6FM Surge Suppressor from Tripp Lite has 6 outlets and a 6-ft. cord with a space-saving right-angle plug. The unit has 3040 joules of surge energy absorption to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. A 6-ft. telephone cord is also included. Diagnostic LEDs alert the user to potential power problems. \$50,000 Ultimate Lifetime Insurance (USA & Canada Only). No warranty cards required for coverage! The Super Surge Alert+Tel comes with child safety covers and color-coded cord identifiers

Applications

• Personal computers, CAD/CAM/CAE workstations, network nodes, fileservers, phone systems, point-of-sale terminals, audio/visual devices, and more.

Package Includes

- TR-6FM Surge Suppressor
- 6 ft. Telephone cord
- Child Safety Covers
- Color-coded cord identifiers
- Warranty information with instruction manual

Features

- 6 outlets with child safety covers
- 6-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment; 6-ft. telephone cord included
- \$50,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment No warranty cards required for coverage!
- Surge energy absorption: 3040 joules; 85,000 amps
- 15 amp circuit breaker
- 3 diagnostic LEDs indicate AC present, line fault & protection present
- EMI/RFI noise filtering
- Logical outlet spacing accommodates transformers without blocking remaining outlets
- Keyhole supports for wall mounting
- Recessed and lighted power switch

- Color-coded cord identifiers
- Lifetime product warranty

Specifications

OVERVIEW		
Intended Application	Home/Office	
OUTPUT		
Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Output volt amp capacity (amps)	15	
Outlet quantity / type	6 NEMA 5-15R	
Transformer accommodation	Holds up to 4 large transformer plugs	
INPUT		
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P input plug	
Input cord length (ft.)	6	
Input cord length (m)	1.8	
Voltage compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Switches	Two position red illuminated on/off power switch	
Diagnostic LEDs	PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	3040	
AC suppression response time	< 1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS)	140	
AC suppression surge current rating	78,500 amps	
UL1499 let through rating	400V - UL Verified	
Immunity	Conforms to IEE 587 / ANSI C62.41	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	Yes	
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		

Shipping weight (lbs)	2.15
Shipping weight (kg)	.98
Unit Dimensions (HWD/in)	1.75 x 3.5 x 9.5
Unit Dimensions (HWD/cm)	4.45 x 8.9 x 24.13
Shipping Dimensions (HWD/in)	13.25 x 6 x 2.25
Shipping Dimensions (HWD/cm)	33.7 x 15.24 x 5.7
Unit weight (Ibs)	1.65
Unit weight (kg)	.75
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
Receptacle Color	Gray
AC line cord color	Gray
Style	Strip
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
FCC Part 68 (Communications)	FCC Part 68
cUL / CSA (Canada)	cUL
Industry Canada (Communications)	Industry Canada
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$50,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModeIID=127.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.