



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SMART3000NET

### SmartPro 3kVA Line Interactive UPS, Extended-run option, Tower, Serial, 120V



#### Highlights

- 3000VA / 3kVA line interactive, extended-run tower UPS
- Maintains 120V nominal output over an input range of 87 to 140V
- Network communications supported via 3 DB9 ports (1 serial / 2 contact closure)
- Current monitoring and switched PDU control via 2 single-outlet load banks
- Input: L5-30P (120V 30A) / Output: 4 NEMA 5-15/20R, 4 NEMA 5-15R (120V)
- 2 year product warranty / \$250,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's SMART 3000NET intelligent, line interactive large tower UPS system protects servers, networking accessories and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Large internal batteries offer 23 minutes half load runtime and 7 minutes fully loaded. Runtime is expandable with optional BP24V28-2U (limit 1) and BP24V70-3U (multi-pack compatible) external battery packs. 3000VA/2400 watt power handling capability supports a variety of networking, telecom and other sensitive electronic applications. Includes 8 protected outlets. Supports remote monitoring of UPS and site power conditions via built-in RS-232 enabled monitoring port, plus standard UPS monitoring via 2 built in contact closure ports. Includes PowerAlert UPS monitoring and unattended shutdown software with complete cabling. Built-in audible alarm and front panel LEDs indicate line power, battery power, battery charge level, load level and voltage regulation status. Network grade AC surge suppression protects equipment from damage and performance problems resulting from transient surges. Two year warranty with \$250,000 [connected e connected equipment insurance](#)

#### Package Includes

- SMART 3000NET UPS System
- PowerAlert Software and three 6 foot network cables
- Warranty information
- Instruction manual

#### Features

- SMART 3000NET line interactive UPS offers battery derived AC output during power outages, voltage regulation during brownouts and overvoltages, plus network-grade AC surge suppression
- 3000VA/2400 watt power handling capability supports a variety of networking, telecom and other sensitive electronic devices
- Large internal batteries offer runtimes of 23 minutes at half load (1500VA/1200 watts) and 7 minutes at full load (3000VA/2400 watts)
- Runtime is further expandable with optional external BP24V28-2U (limit 1) and BP24V70-3U (multi-pack compatible) battery packs
- Automatic Voltage Regulation (AVR) circuits maintain 120V nominal output over an input voltage range of 87-140V
- Includes 8 fully protected outlets (4 NEMA 5-15R & 4 NEMA 5-15/20R) with 2 single outlet load banks that can be individually powered off and back on again via software interface
- PowerAlert UPS monitoring and unattended shutdown software enables configurable network broadcast messaging, email notification, event logging and running user defined script commands
- Offers simultaneous monitoring of up to 3 directly connected devices through included DB9 contact closure and RS-232 enabled interfaces, or the monitoring of any number of additional servers over IP with included PowerAlert monitoring software

- In addition to the contact closure monitoring of on battery, low battery and power restored messaging, built-in RS-232 interface supports messaging of UPS and line power status, including AC line voltage, DC battery voltage and remaining battery capacity
- Supports activate self-test and UPS output power control for delayed or immediate reboot of connected equipment
- Diagnostic LEDs (indicate 17 performance conditions)
- UL (USA), cUL (Canada), NOM (Mexico), FCC Class A (Emissions)
- \$250,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only)

## Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	3000
Output kVA capacity (kVA)	3
Output Watt Capacity (watts)	2400
Output kW capacity	2.4
Output power factor	0.8
Nominal Output Voltage(s) Supported	120V
Frequency compatibility	60 Hz
Output voltage regulation (line mode)	-13% / +5%
Output voltage regulation (Battery mode)	+/- 5%
Built-in UPS output receptacles	4 5-15R outlet(s); 4 5-15/20R outlet(s)
Built-in controllable switched load banks	Three switchable single-outlet 5-15R load banks
Output circuit breaker	15A branch rated (x2) - each breaker protects 4 outlets
Basic PDU options	<a href="#">PDU1220</a> (1U / 13 5-15/20R outlets); <a href="#">PDUNV</a> (1U / 2 C19, 12 C13 outlets); <a href="#">PDUV20</a> (0U / 12 5-15/20R outlets); <a href="#">PDU40TDUAL</a> (0U / 40 5-15/20R outlets)
Metered PDU options	<a href="#">PDUMH20</a> (1U / 13 5-15/20R outlets); <a href="#">PDUMH20AT</a> (1U / 16 5-15/20R outlets)*; <a href="#">PDUMV20</a> (0U / 16 5-15/20R outlets); <a href="#">PDUMV40</a> (0U / 32 5-15/20R outlets)
Switched PDU options	<a href="#">PDUMH20ATNET</a> (1U / 16 5-15/20R outlets)*; <a href="#">PDUMV20NET</a> (0U / 24 5-15/20R outlets)
External PDU redundancy options	*Auto Transfer Switch features utilizing the secondary PDU input cord are compatible with Smart Online UPS models only
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	PWM sine wave
INPUT	
Rated input current (at maximum load)	22A
Nominal Input Voltage(s) Supported	120V AC

<b>UPS input connection type</b>	L5-30P
<b>UPS Input cord length (ft.)</b>	8
<b>UPS Input cord length (m)</b>	2.4
<b>Recommended Electrical Service</b>	30A 120V
<b>Input cord length (ft.)</b>	8
<b>Input cord length (m)</b>	2.4
<b>BATTERY</b>	
<b>Full load runtime (minutes)</b>	7 min. (2400w)
<b>Half load runtime (minutes)</b>	23 min. (1200w)
<b>Expandable battery runtime</b>	Extended runtime supported via optional external battery packs
<b>External battery pack compatibility</b>	<a href="#">BP24V28-2U</a> (limit 1); <a href="#">BP24V70-3U</a> (multi-pack compatible)
<b>DC system voltage (VDC)</b>	24
<b>Battery recharge rate (included batteries)</b>	Less than 9 hours from 10% to 90%
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description</b>	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 87 to 140
<b>Overvoltage correction</b>	Input voltages between 127 and 140 are reduced by 12%
<b>Undervoltage correction</b>	Input voltages between 95 and 105 are boosted by 10%
<b>Severe undervoltage correction</b>	Input voltages between 87 and 94 are boosted by 22%
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>LED Indicators</b>	5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status
<b>Alarms</b>	Audible alarm indicates power-failure and low-battery conditions
<b>Alarm cancel operation</b>	Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status
<b>Switches</b>	2 Switches control off/on power status and alarm-cancel/self-test operation; set of 4 rear-panel switches control system enable and contact closure port inverter shutoff commands
<b>SURGE / NOISE SUPPRESSION</b>	
<b>UPS AC suppression joule rating</b>	480
<b>UPS AC suppression response time</b>	Instantaneous
<b>EMI / RFI AC noise suppression</b>	Yes
<b>PHYSICAL</b>	

Installation form factors supported with included accessories	Tower
Primary form factor	Tower
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	17 x 9 x 12.5
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	43.2 x 22.9 x 31.8
UPS / Power Module weight (lbs)	89
UPS / Power Module weight (kg)	40.4
UPS Shipping dimensions (height x width x depth / inches)	22.2 x 12.8 x 16.5
UPS Shipping dimensions (height x width x depth / cm)	56.5 x 32.4 x 41.9
Shipping weight (lbs)	96
Shipping weight (kg)	43.6
UPS housing material	PVC
Cooling method	Fan
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	82.4
Battery mode BTU / hr. (full load)	1219.3
<b>COMMUNICATIONS</b>	
Communications interface	DB9 Serial; Contact closure
Network monitoring port description	Supports detailed monitoring of UPS and site power conditions; contact closure communications via two additional DB9 ports (3 total)
PowerAlert software	Included
Communications cable	3 DB9 cables included
<b>LINE / BATTERY TRANSFER</b>	
Transfer time	2-4 milliseconds
Low voltage transfer to battery power (setpoint)	87

High voltage transfer to battery power (setpoint)	140
<b>SPECIAL FEATURES</b>	
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
Green & high efficiency features	Individually controllable load banks
<b>CERTIFICATIONS</b>	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI)
<b>WARRANTY</b>	
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 Ultimate Lifetime Insurance

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
External Battery Packs	<a href="#">BP24V28-2U</a>	BP24V28-2U - External Battery Pack for UPS System	-
External Battery Packs	<a href="#">BP24V70-3U</a>	BP24V70-3U - External Battery Pack for UPS System	-
Surge Protectors	<a href="#">DNET1</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Surge Protectors	<a href="#">DTEL2</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Extended Warranties	<a href="#">WEXT3-2200-3000</a>	3-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 2200-3000VA	-
Extended Warranties	<a href="#">WEXT5-2200-3000</a>	5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 2200-3000VA or less	-
Power Distribution	<a href="#">RS-1215-20</a>	Tripp Lite Power Strip - Multiple outlets wherever you need them	-
Power Distribution	<a href="#">RS-1215</a>	Tripp Lite Power Strip - Multiple outlets wherever you need them	-
Power Distribution	<a href="#">PDU1220</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	-
Power Distribution	<a href="#">PDU1215</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=44](http://www.tripplite.com/en/products/model.cfm?txtModelID=44).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.