



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SMART3000RM2U

SmartPro 3kVA Line Interactive Sine Wave UPS, Extended-run & SNMPWEBCARD options, 2U Rack/Tower, USB, Serial, EPO, 120V



Highlights

- 3000VA / 3kVA high efficiency line interactive, extended-run 2U rack / tower UPS
- Maintains sine-wave 120V nominal output over an input range of 83 to 145V
- Network communications supported via HID enabled USB port, DB9 serial port, SNMP/Web card slot and EPO interface
- Current monitoring and switched PDU control via 3 individually controllable load banks
- Input: NEMA L5-30P (120V 30A) / Output: 1 L5-30R, 8 NEMA 5-15/20R (120V)
- 2 year product warranty / \$250,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Description

3000VA line interactive UPS system for server, network and telecommunications equipment. 2U rackmount or tower form factor with an installed depth of only 19 inches. High 96% line-power efficiency rating reduces energy consumption and BTU heat output. Expandable battery runtime with optional BP48V24-2U and BP48V60RT-3U external battery packs. Uninterruptible Power Supply (UPS) switches to battery-derived AC output during power failures and extreme voltage variations. Line interactive Automatic Voltage Regulation (AVR) offers two levels of voltage boost during brownouts and one level of voltage cut during overvoltages to maintain regulated 120v output over an input range of 83-145V. Includes L5-30P input plug and both 5-15/20R and L5-30R output receptacles. Network-grade AC surge and noise suppression. Network management interfaces support communications via USB, DB9 serial and SNMPWEBCARD slot. HID-compliant USB interface enables full integration with built-in power management and auto shutdown features of Windows and Mac OS X. Supports simultaneous detailed monitoring of equipment load levels, self-test data and utility power conditions via all 3 network interfaces at once. Includes PowerAlert monitoring software and complete cabling. Emergency Power Off (EPO) interface. Integrated 3-bank PDU switching supports load shedding and remote-reboot of connected equipment. 3-stage metered current monitoring and battery charge status LEDs. Utility power and voltage regulation LEDs. Audible alarm. Self-test. 4-post rackmount accessories included; 2-9U STAND tower kit and 2POSTRMKITWM two post rack & wallmount accessories available. Field-replaceable, hot-swappable internal batteries and external battery packs. Attractive all-black color scheme. 2-year warranty and \$250,000 connected equipment insurance; extended warranty and service contracts available.

Package Includes

- SMART3000RM2U UPS System, PowerAlert Software and cabling, 4-post rackmount installation hardware, Warranty information, Instruction manual

Features

- SmartPro line interactive UPS system is ideal for voice, data, medical and industrial networking applications
- High 96% line-power efficiency rating reduces energy consumption and BTU heat output
- Line interactive Automatic Voltage Regulation (AVR) offers two levels of voltage boost during brownouts and one level of voltage cut during overvoltages
- Maintains continuous operation through blackouts, voltage fluctuations and surges

- Corrects line voltage conditions as low as 83V and as high as 145 back to 120V nominal values
- Standard internal battery set offers 12 minutes at half load and 4 minutes at full load
- Optional BP48V24-2U and BP48V60RT3U external rack/tower battery packs enable extended runtime operation
- Compact form factor installs using only 2 rack spaces (2U) with a maximum installed depth of only 19 inches
- Ships with all mounting accessories for 4 post rackmount installation
- Optional 2POSTRMKITWM enables 2 post rackmount or wallmount installation
- Optional 2-9USTAND accessory enables small-footprint upright tower placement
- Network interfaces support simultaneous communications via built-in USB, DB9 serial and SNMPWEBCARD slot
- HID compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- Included PowerAlert UPS monitoring software supports safe unattended shutdown, monitoring and control via local connected servers, with the built-in ability to shutdown any number of additional servers over IP
- UPS interface supports on-battery, low-battery, power-restored, AC-voltage, DC-voltage, output current monitoring, battery charge current, battery capacity, AC line frequency, timed inverter shutoff, activate self-test, load bank output power control and remote reboot
- Built-in Emergency Power Off (EPO) interface with cable
- L5-30P input plug
- 5-15/20R and L5-30R output receptacles
- Integrated 3 bank switched PDU enables remote outlet management for load shedding or remote reboot of individual load banks (1 outlet per load bank)
- Front panel LEDs offer current monitoring and battery charge level information
- UPS ships fully assembled in full compliance with DOT regulations, no time consuming connection of internal batteries by user required
- 2 year manufacturer's product warranty, \$250,000 Ultimate Lifetime Insurance

Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	3000
Output kVA capacity (kVA)	3
Output Watt Capacity (watts)	2250
Output kW capacity	2.2
Output power factor	0.8
Nominal Output Voltage(s) Supported	120V
Frequency compatibility	60 Hz
Output voltage regulation (line mode)	-18%, +8%
Output voltage regulation (Battery mode)	+/- 5%
Built-in UPS output receptacles	8 5-15/20R outlet(s); 1 L5-30R outlet(s)
Built-in controllable switched load banks	Three switchable single-outlet 5-15/20R load banks
Output circuit breaker	20A (x2) - each breaker protects 4 5-15/20R outlets, L5-30R is unbreakered
Basic PDU options	PDU2430 (1U / 24 5-15R outlets)
Metered PDU options	PDUMV30 (0U / 24 5-15/20R outlets)
Switched PDU options	PDU MH30NET (2U / 16 5-15/20R outlets); PDU MV30NET (0U / 24 5-15/20R outlets)
Output AC waveform (AC mode)	Sine wave

Output AC waveform (battery mode)	Pure Sine wave
INPUT	
Rated input current (at maximum load)	24A
Nominal Input Voltage(s) Supported	120V AC
UPS input connection type	L5-30P
Input circuit breaker	30A
UPS Input cord length (ft.)	10
UPS Input cord length (m)	3
Recommended Electrical Service	30A 120V
BATTERY	
Full load runtime (minutes)	4 min. (2250w)
Half load runtime (minutes)	11 min. (1125w)
Expandable battery runtime	Extended runtime supported via optional external battery packs
External battery pack compatibility	BP48V24-2U (limit 1); BP48V60RT3U (multi-pack compatible)
DC system voltage (VDC)	48
Battery recharge rate (included batteries)	Less than 4.5 hours from 10% to 90%
Replacement battery cartridge (internal UPS battery replacement)	RBC94-2U
Battery Access	Front panel battery access door
Battery replacement description	Hot-swappable, user replaceable batteries
VOLTAGE REGULATION	
Voltage regulation description	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 79 to 147
Overvoltage correction	Input voltages between 128 and 147 are reduced by 12%
Undervoltage correction	Input voltages between 95 and 104 are boosted by 12%
Severe undervoltage correction	Input voltages between 79 and 94 are boosted by 24%
LEDS ALARMS & SWITCHES	
LED Indicators	5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status
Alarms	Audible alarm indicates power-failure, overload and low-battery conditions
Alarm cancel operation	Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation
SURGE / NOISE SUPPRESSION	

UPS AC suppression joule rating	570
UPS AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Installation form factors supported with included accessories	4 post 19 inch rackmount (mounting rail kit included)
Installation form factors supported with optional accessories	2 post rackmount (2POSTRMKITWM); Wallmount (2POSTRMKITWM); Tower (2-9USTAND)
Primary form factor	Rackmount
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	3.5 x 17.5 x 19
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	8.9 x 44.4 x 48.3
Installed whole system total rack space height (rack spaces)	2U
Secondary form factor	Tower (requires 2-9USTAND)
Installed whole system dimensions in secondary form factor (height x width x depth / inches)	17.5 x 3.5 x 19
UPS dimensions in secondary form factor (height x width x depth / cm)	44.4 x 8.9 x 48.3
UPS / Power Module weight (lbs)	64
UPS / Power Module weight (kg)	29.1
UPS Shipping dimensions (height x width x depth / inches)	9 x 23.5 x 20
UPS Shipping dimensions (height x width x depth / cm)	22.9 x 59.7 x 50.8
Shipping weight (lbs)	72
Shipping weight (kg)	32.7
UPS housing material	Steel
Cooling method	Fan
ENVIRONMENTAL	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius

Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	318.8
Battery mode BTU / hr. (full load)	1457.1
COMMUNICATIONS	
Communications interface	USB (HID enabled); DB9 Serial; Contact closure
Network monitoring port description	Supports detailed monitoring of UPS and site power conditions; 1 USB port and 1 DB9 serial contact closure port
PowerAlert software	Included
Communications cable	USB and DB9 cabling included
WatchDog compatibility	Supports Watchdog application, OS and hard-reboot restart options for remote applications
LINE / BATTERY TRANSFER	
Transfer time	5 milliseconds
Low voltage transfer to battery power (setpoint)	83
High voltage transfer to battery power (setpoint)	145
SPECIAL FEATURES	
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
High availability UPS features	Hot swappable batteries
Green & high efficiency UPS features	Greater than 95% efficiency - GREEN UPS; Individually controllable load banks
CERTIFICATIONS	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI)
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 Ultimate Lifetime Insurance

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Surge Protectors	DTEL2	Network Surge Suppressor - Essential protection for data and communication lines	-
Tower Stands	2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	-

Surge Protectors	DNET1	Network Surge Suppressor - Essential protection for data and communication lines	-
Extended Warranties	WEXT3-2200-3000	3-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 2200-3000VA	-
Extended Warranties	WEXT5-2200-3000	5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 2200-3000VA or less	-
Power Distribution	PDU1220	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	-
Power Distribution	PS7224-20	Tripp Lite Power Strip - Multiple outlets wherever you need them	-
External Battery Packs	BP48V60RT-3U	External Battery Pack and Cable. 3U, Expandable, Blue 2-Point Connector	-
External Battery Packs	BP48V24-2U	BP48V242U - External Battery Pack for UPS System	-
SNMP Accessories	SNMPWEBCARD	For remote monitoring and control via SNMP, Web, or Telnet.	-
SNMP Accessories	ENVIROSENSE	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	-
USB Hubs/Accessories	U022-010	10-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	-
Rackmount/Wallmount Kits	2POSTRMKITWM	Enables 2-Post Rackmount or Wallmount Installation of Select Rackmount UPS Systems	-
Audio Cables	CT120	Instant-Read- AC Outlet Circuit Tester	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3025.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.