



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SMART750SLT

**SmartPro .75kVA Line Interactive Sine Wave UPS, SNMPWEBCARD option, Tower, USB, Serial, 100/110/120V**



### Highlights

- 750VA line interactive tower UPS
- Maintains sine-wave 100, 110 or 120V nominal output over an input range of 83 to 145V
- Network communications supported via USB port, serial port, SNMP/Web card slot
- Current monitoring, single line TEL/DSL or ethernet line surge suppression and four surge-only outlets
- Input: NEMA 5-15P (120V 15A) / Output: 8 NEMA 5-15R (120V)
- 2 year product warranty / \$250,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

### Description

Tripp Lite's SMART750SLT intelligent, line-interactive sine wave UPS system protects servers, networking accessories and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Large internal batteries offer 15 minutes half load runtime and 5 minutes fully loaded. 750VA/500 watt power handling capability and full-time sine wave output offers guaranteed compatibility with networking, telecom and other sensitive electronic applications. Includes 8 protected NEMA 5-15R output receptacles total, 4 of which offer surge suppression-only for less critical desktop accessories. Supports simultaneous remote monitoring of UPS and site power conditions via built-in network accessory card slot, USB and DB9 serial monitoring ports. Optional SNMPWEBCARD accessory enables remote monitoring of UPS as a managed device via network management console applications. Communications interfaces support messaging of UPS and line power status, plus output power control for delayed or immediate reboot of all connected devices at once. Includes PowerAlert UPS monitoring and unattended shutdown software with management support for an unlimited number of network UPS systems. Built-in audible alarm and 10 LEDs offer status notification for line power, battery power, battery charge level, load level, plus AVR boost and trim operational status information. Network grade AC surge suppression protects equipment from damage and performance problems resulting from transient surges. Also includes single line TEL/DSL or Ethernet line surge suppression. Attractive, all-black tower housing. Two year warranty with \$250,000 [Ultimate Lifetime Insurance](#).

### Package Includes

- SMART750SLT UPS System
- PowerAlert Software CD-Rom
- USB and serial cabling
- User manual with warranty information

### Features

- SMART750SLT line-interactive UPS offers battery derived sine wave AC output during power outages, voltage regulation during brownouts and overvoltages, plus network-grade AC surge suppression
- 750VA/500 watt power handling capability with full-time sine wave output offers guaranteed compatibility with networking, telecom and other sensitive electronic devices
- Large internal batteries offer runtimes of 15 minutes at half load (375VA/250 watts) and 5 minutes at full load (750VA/500 watts)
- Automatic Voltage Regulation (AVR) circuits maintain user-selectable 100, 110 or 120V nominal output over an input voltage range of 83 to 145V

- Includes 8 NEMA 5-15R output receptacles total, 4 with UPS and surge suppression for critical devices and 4 with surge-only protection for less critical accessories
- PowerAlert UPS monitoring and unattended shutdown software enables configurable network broadcast messaging, email notification, event logging and running user-defined script commands
- Offers simultaneous monitoring by up to 3 directly-connected devices through included USB, DB9 and SNMP\* interfaces (\*requires optional SNMPWEBCARD), or the monitoring of any number of additional UPS systems over IP with included PowerAlert monitoring software.
- Communications ports support messaging of UPS and line power status, including on-battery, low-battery, power restored, AC line voltage, DC battery voltage and remaining battery capacity
- Supports timed inverter shutoff after unattended shutdown, activate self-test and UPS output power control for delayed or immediate reboot of connected equipment
- Supports Tripp Lite's WatchDog software application to restore unresponsive programs by systematically restarting applications, operating systems and ultimately rebooting completely locked computers by momentarily switching UPS power off and back on again (requires optional WATCHDOGSW)
- 10 LEDs offer continuous status information of UPS operating parameters and site power quality
- Hot-swappable batteries allow on-site battery replacement without powering off connected equipment
- Single line TEL/DSL and network Ethernet line surge suppression
- UL (USA), cUL (Canada), NOM (Mexico), FCC Class B (Emissions) Listed
- 2 year warranty with up to \$250,000 [connected equipment insurance](#)

## Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	750
Output Watt Capacity (watts)	500
Output power factor	0.7
Nominal Output Voltage(s) Supported	100V; 110V; 120V
Nominal Voltage details	120V default (voltage selection via back panel switches)
Frequency compatibility	50 / 60 Hz
Output voltage regulation (line mode)	-13%, +15%
Output voltage regulation (Battery mode)	+/- 5%
Built-in UPS output receptacles	8 5-15R outlet(s)
Surge suppression only outlets	4 UPS outlets, 4 surge-only outlets
Basic PDU options	<a href="#">PDU1215</a> (1U / 13 5-15R outlets); <a href="#">PDUNV</a> (1U / 2 C19, 12 C13 outlets); <a href="#">PDU1415</a> (0U / 14 5-15R outlets); <a href="#">PDUV15</a> (0U / 12 5-15R outlets)
Metered PDU options	<a href="#">PDUMH15</a> (1U / 13 5-15R outlets); <a href="#">PDUMH15AT</a> (1U / 8 5-15R outlets)*; <a href="#">PDUMV15</a> (0U / 16 5-15R outlets)
Switched PDU options	<a href="#">PDUMH15ATNET</a> (1U / 8 5-15R outlets)*; <a href="#">PDUMV15NET</a> (0U / 16 5-15R outlets)
External PDU redundancy options	*Auto Transfer Switch features utilizing the secondary PDU input cord are compatible with Smart Online UPS models only
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	Pure Sine wave
INPUT	

Rated input current (at maximum load)	12A
Nominal Input Voltage(s) Supported	100V AC; 110V AC; 120V AC
UPS input connection type	5-15P
UPS Input cord length (ft.)	6
UPS Input cord length (m)	1.8
Recommended Electrical Service	15A 120V
<b>BATTERY</b>	
Full load runtime (minutes)	5 min. (500w)
Half load runtime (minutes)	15 min. (250w)
DC system voltage (VDC)	24
Battery recharge rate (included batteries)	Less than 8 hours from 10% to 90%
Replacement battery cartridge (internal UPS battery replacement)	<a href="#">RBC51</a> (quantity 2)
Battery Access	Battery access door
Battery replacement description	Hot-swappable, user replaceable batteries
<b>VOLTAGE REGULATION</b>	
Voltage regulation description	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 83 to 145 (120v), 87 to 133 (110v), 83 to 121 (100v)
Overvoltage correction	Voltage reduction of 12% applies when input is 127 to 145 (120v), 116 to 133 (110v), 106 to 121 (100v)
Undervoltage correction	Voltage boost of 17% applies when input is 96 to 108 (120v), 87 to 99 (110v), 83 to 90 (100v)
Severe undervoltage correction	Voltage boost of 32% applies when input is 83 to 95 (120v only)
<b>LEDS ALARMS &amp; SWITCHES</b>	
LED Indicators	9 LEDs indicate line power, battery power, AVR, overload and replace battery status - with a 3-LED level meter for load and battery charge level
Site wiring fault indication	Rear panel site wiring fault LED
Alarms	Audible alarm indicates power failure and overload conditions
Alarm cancel operation	Power-fail alarm can be silenced using alarm-cancel switch
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation; rear panel protected switches support nominal voltage selection
<b>SURGE / NOISE SUPPRESSION</b>	
UPS AC suppression joule rating	480
UPS AC suppression response time	Instantaneous

<b>UPS Dataline suppression</b>	1 line TEL/DSL (1 in / 1 out); 10/100Base T Ethernet
<b>EMI / RFI AC noise suppression</b>	Yes
<b>PHYSICAL</b>	
<b>Installation form factors supported with included accessories</b>	Tower
<b>Primary form factor</b>	Tower
<b>UPS / Power Module dimensions in primary form factor (height x width x depth / inches)</b>	10.2 x 6.8 x 9
<b>UPS / Power Module dimensions in primary form factor (height x width x depth / cm)</b>	26 x 17.1 x 22.9
<b>UPS / Power Module weight (lbs)</b>	30
<b>UPS / Power Module weight (kg)</b>	13.6
<b>UPS Shipping dimensions (height x width x depth / inches)</b>	13.8 x 9.8 x 13.2
<b>UPS Shipping dimensions (height x width x depth / cm)</b>	34.9 x 24.8 x 33.7
<b>Shipping weight (lbs)</b>	32
<b>Shipping weight (kg)</b>	14.5
<b>UPS housing material</b>	Steel
<b>Cooling method</b>	Fan
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature Range</b>	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
<b>Storage Temperature Range</b>	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
<b>Relative Humidity</b>	0 to 95%, non-condensing
<b>AC mode BTU / hr. (full load)</b>	70.8
<b>Battery mode BTU / hr. (full load)</b>	728.6
<b>Audible Noise</b>	Audible Noise < 50 dBA at Front Side 1 Meter
<b>COMMUNICATIONS</b>	
<b>Communications interface</b>	USB; DB9 Serial; Slot for SNMP/Web interface
<b>Network monitoring port description</b>	Supports detailed monitoring of UPS and site power conditions
<b>PowerAlert software</b>	Included

<b>Communications cable</b>	USB and DB9 cabling included
<b>WatchDog compatibility</b>	Supports Watchdog application, OS and hard-reboot restart options for remote applications
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time</b>	4-8 milliseconds
<b>Low voltage transfer to battery power (setpoint)</b>	95V (120V), 87V (110V), 83V (100V)
<b>High voltage transfer to battery power (setpoint)</b>	145V (120V), 133V (110V), 121V (100V)
<b>SPECIAL FEATURES</b>	
<b>Cold Start (startup in battery mode during a power failure)</b>	Cold-start operation supported
<b>High availability UPS features</b>	Hot swappable batteries
<b>Green &amp; high efficiency features</b>	Greater than 95% efficiency - GREEN UPS
<b>CERTIFICATIONS</b>	
<b>UPS Certifications</b>	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico)
<b>UPS Certification details</b>	EMI approvals: Yes
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	2-year limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$250,000 Ultimate Lifetime Insurance

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Surge Protectors	<a href="#">DNET1</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Surge Protectors	<a href="#">DTEL2</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Extended Warranties	<a href="#">WEXT3-500-1500</a>	3-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less	-
Extended Warranties	<a href="#">WEXT5-500-1500</a>	5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less	-
Power Distribution	<a href="#">PDU1215</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	-
SNMP Accessories	<a href="#">SNMPWEBCARD</a>	For remote monitoring and control via SNMP, Web, or Telnet.	-
SNMP Accessories	<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	-
USB Hubs/Accessories	<a href="#">U022-010</a>	10-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	-
Software	<a href="#">WATCHDOGSW</a>	WatchDog Service Monitoring / Reboot Software	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3007](http://www.tripplite.com/en/products/model.cfm?txtModelID=3007).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.