

# MLC

MLC - ideal for general-purpose settings and as supplementary task lighting in patient rooms. A 9.5 in. (241 mm) diameter shade with inner reflector and 6-ring louver eliminates glare and protects against bulb breakage. Heavy duty, 20-gauge, CRS K-arm with 0.5 in. (13 mm) square tubing and internal tempered steel springs assures proper balance and ease of movement while providing optimal durability.



- 9.5 in. (241 mm) diameter shade with inner reflector
- 6-ring louver
- Heavy-duty, 20-gauge, CRS K-arm
- UL/CUL Listed
- Mounting options sold separately
- Color: Light Grey, White

## RELATED PRODUCTS

---



MLS

## CODES

## MLC100 - 5FT. CORD LENGTH

Article Number	Light Source	Weight	Arm Length	Mount	Ctn. Colors
14250WT	22W Fluorescent and 60W Incandescent	4.0	1143	Wall mount 1	<input type="checkbox"/>

## MLC100S - 18IN. CORD LENGTH

Article Number	Light Source	Weight	Arm Length	Mount	Ctn. Colors
14251LG	22W Fluorescent and 60W Incandescent	4.0	1143	Wall mount sold separately 1	<input checked="" type="checkbox"/>
14251WT	22W Fluorescent and 60W Incandescent	4.0	1143	Wall mount sold separately 1	<input type="checkbox"/>

## MLC145 - 5FT. CORD LENGTH \*\*\*LIMITED QUANTITIES AVAILABLE\*\*\*

Article Number	Light Source	Weight	Arm Length	Mount	Ctn. Colors
14255LG	22W Fluorescent and 60W Incandescent	4.0	1143	Edge/Floor mount sold separately 1	<input checked="" type="checkbox"/>
14255WT	22W Fluorescent and 60W Incandescent	4.0	1143	Edge/Floor mount sold separately 1	<input type="checkbox"/>

## MLC150S - 18IN. CORD LENGTH

Article Number	Light Source	Weight	Arm Length	Mount	Ctn. Colors
14261LG	22W Fluorescent and 60W Incandescent	4.0	1270	Wall mount sold separately 1	<input checked="" type="checkbox"/>
14261WT	22W Fluorescent and 60W Incandescent	4.0	1270	Wall mount sold separately 1	<input type="checkbox"/>

## ACCESSORIES

Wall Mount SP-4 Bracket  
34" Floor Stand (for use with

## DESIGNATION

50031  
50036