

4

3







2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL INTERNATIONAL RIGHTS RESERVED.

LOC	DISP	REVISIONS					
		P	LYR	DESCRIPTION	DATE	BY	APPD
CE	00	D		ECR-10-001039	25JUN2016	JZ	RZ

PERFORMANCE REQUIREMENTS:
 OPERATING WAVELENGTH: 1260-1360 & 1430-1625nm
 REFLECTANCE: AVG. -55dB
 OPERATING TEMPERATURE: -40°C TO +85°C
 ATTENUATION TOLERANCE, AMBIENT:
 FOR 0 dB ATTENUATORS: +0.5dB MAX
 FOR ATTENUATORS < 5dB: ±0.5dB
 FOR ATTENUATORS ≥ 5dB: ±10% OF NOMINAL ATTENUATION VALUE
 MEASURED WITH REFERENCE QUALITY LAUNCH LEADS:
 - REFLECTANCE: ≤ -60dB
 - FIBER CORE ECCENTRICITY < 0.3um



20	2-1693560-0
19	1-1693560-9
18	1-1693560-8
17	1-1693560-7
16	1-1693560-6
15	1-1693560-5
14	1-1693560-4
13	1-1693560-3
12	1-1693560-2
11	1-1693560-1
10	1-1693560-0
9	1693560-9
8	1693560-8
7	1693560-7
6	1693560-6
5	1693560-5
4	1693560-4
3	1693560-3
2	1693560-2
1	1693560-1
0	9-1693560-9
NOMINAL ATTENUATION VALUE (dB)	PART NUMBER

<small>THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION. ALL RIGHTS RESERVED. © 2016 TYCO ELECTRONICS CORPORATION. ALL INTERNATIONAL RIGHTS RESERVED.</small>		DWG: E. MCCORMICK CDR: S. HOPKINS APPD: S. BUCHTER DATE: 01 NOV 2006	NAME: S. BUCHTER PRODUCT SPEC: 108-2221 APPLICATION SPEC: 114-1129 WEIGHT: - FINISH: -	DATE: 01 NOV 2006 NAME: S. BUCHTER PRODUCT SPEC: 108-2221 APPLICATION SPEC: 114-1129 WEIGHT: - FINISH: -	Tyco Electronics Corporation Shanghai, China	ATTENUATOR, OPTICAL, BUILD OUT, SM, LC/UPC, BROADBAND, BANDPASS	SIZE: A2 CASE CODE: 00779 DRAWING NO: 1693560	RESTRICTED TO: - SCALE: 3:1 SHEET: 1 OF 1 REV: D
--	--	---	--	---	---	---	---	---