

GaAs-IR-Lumineszenzdiode
GaAs Infrared Emitter
Lead (Pb) Free Product - RoHS Compliant

LD 274



Wesentliche Merkmale

- GaAs-LED mit sehr hohem Wirkungsgrad
- Hohe Zuverlässigkeit
- Gute spektrale Anpassung an Si-Fotoempfänger
- Gehäusegleich mit SFH 484

Anwendungen

- IR-Fernsteuerung von Fernseh- und Rundfunkgeräten, Videorecordern, Lichtdimmern
- Gerätefernsteuerungen für Gleich- und Wechsellichtbetrieb
- Sensorik
- Diskrete Lichtschranken

Features

- Very highly efficient GaAs-LED
- High reliability
- Spectral match with silicon photodetectors
- Same package as SFH 484

Applications

- IR remote control of hi-fi and TV-sets, video tape recorders, dimmers
- Remote control for steady and varying intensity
- Sensor technology
- Discrete interrupters

Typ Type	Bestellnummer Ordering Code	Gehäuse Package
LD 274	Q62703Q1031	5-mm-LED-Gehäuse ($T\ 1\ \frac{3}{4}$), graugetöntes Epoxy-Gießharz, Anschlüsse im 2.54-mm-Raster ($\frac{1}{10}$ "), Kathodenkennzeichnung: Kürzerer Lötspieß, flat
LD 274-2 ¹⁾	Q62703Q1819	
LD 274-3	Q62703Q1820	5 mm LED package ($T\ 1\ \frac{3}{4}$), grey colored epoxy resin lens, solder tabs lead spacing 2.54 mm ($\frac{1}{10}$ "), cathode marking: shorter solder lead, flat

¹⁾ Nur auf Anfrage lieferbar.

¹⁾ Available only on request.

Grenzwerte ($T_A = 25^\circ\text{C}$)**Maximum Ratings**

Bezeichnung Parameter	Symbol Symbol	Wert Value	Einheit Unit
Betriebs- und Lagertemperatur Operating and storage temperature range	$T_{\text{op}}, T_{\text{stg}}$	-40 ... +100	°C
Sperrspannung Reverse voltage	V_R	5	V
Durchlassstrom Forward current	I_F	100	mA
Stoßstrom, $t_p = 10 \mu\text{s}, D = 0$ Surge current	I_{FSM}	3	A
Verlustleistung Power dissipation	P_{tot}	165	mW
Wärmewiderstand Thermal resistance	R_{thJA}	450	K/W

Kennwerte ($T_A = 25^\circ\text{C}$)**Characteristics**

Bezeichnung Parameter	Symbol Symbol	Wert Value	Einheit Unit
Wellenlänge der Strahlung Wavelength at peak emission $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$	λ_{peak}	950	nm
Spektrale Bandbreite bei 50% von I_{max} Spectral bandwidth at 50% of I_{max} $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$	$\Delta\lambda$	55	nm
Abstrahlwinkel Half angle	ϕ	±10	Grad
Aktive Chipfläche Active chip area	A	0.09	mm ²
Abmessungen der aktiven Chipfläche Dimension of the active chip area	$L \times B$ $L \times W$	0.3 × 0.3	mm ²
Abstand Chipoberfläche bis Linsenscheitel Distance chip front to lens top	H	4.9 ... 5.5	mm
Schaltzeiten, I_e von 10% auf 90% und von 90% auf 10%, bei $I_F = 100 \text{ mA}, R_L = 50 \Omega$ Switching times, I_e from 10% to 90% and from 90% to 10%, $I_F = 100 \text{ mA}, R_L = 50 \Omega$	t_r, t_f	0.5	μs

Kennwerte ($T_A = 25^\circ\text{C}$)**Characteristics (cont'd)**


Bezeichnung Parameter	Symbol Symbol	Wert Value	Einheit Unit
Kapazität Capacitance $V_R = 0 \text{ V}, f = 1 \text{ MHz}$	C_o	25	pF
Durchlassspannung Forward voltage $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$ $I_F = 1 \text{ A}, t_p = 100 \mu\text{s}$	V_F V_F	1.30 (≤ 1.5) 1.90 (≤ 2.5)	V V
Sperrstrom, $V_R = 5 \text{ V}$ Reverse current	I_R	0.01 (≤ 1)	μA
Gesamtstrahlungsfluss Total radiant flux $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$	Φ_e	20	mW
Temperaturkoeffizient von I_e bzw. Φ_e , $I_F = 100 \text{ mA}$ Temperature coefficient of I_e or Φ_e , $I_F = 100 \text{ mA}$	TC_I	- 0.55	%/K
Temperaturkoeffizient von V_F , $I_F = 100 \text{ mA}$ Temperature coefficient of V_F , $I_F = 100 \text{ mA}$	TC_V	- 1.5	mV/K
Temperaturkoeffizient von λ , $I_F = 100 \text{ mA}$ Temperature coefficient of λ , $I_F = 100 \text{ mA}$	TC_λ	+ 0.3	nm/K

Gruppierung der Strahlstärke I_e in Achsrichtunggemessen bei einem Raumwinkel $\Omega = 0.001 \text{ sr}$ **Grouping of Radiant Intensity I_e in Axial Direction**at a solid angle of $\Omega = 0.001 \text{ sr}$


Bezeichnung Parameter	Symbol Symbol	Wert Value			Einheit Unit
		LD 274	LD 274-2 ¹⁾	LD 274-3	
Strahlstärke Radiant intensity $I_F = 100 \text{ mA}, t_p = 20 \text{ ms}$	$I_{e \min}$ $I_{e \max}$	50 —	50 100	80 —	mW/sr mW/sr
Strahlstärke Radiant intensity $I_F = 1 \text{ A}, t_p = 100 \mu\text{s}$	$I_{e \text{ typ.}}$	700	600	800	mW/sr

¹⁾ Nur auf Anfrage lieferbar.¹⁾ Available only on request.


Relative Spectral Emission
 $I_{\text{rel}} = f(\lambda)$



Forward Current
 $I_F = f(V_F)$, single pulse, $t_p = 20 \mu\text{s}$




Radiation Characteristics,
 $I_{\text{rel}} = f(\varphi)$




Radiant Intensity $\frac{I_e}{I_e \text{ } 100 \text{ mA}} = f(I_F)$


Single pulse, $t_p = 20 \mu\text{s}$




Max. Permissible Forward Current
 $I_F = f(T_A)$



Permissible Pulse Handling Capability $I_F = f(\tau)$, $T_C \leq 25 \text{ } ^\circ\text{C}$, duty cycle $D = \text{parameter}$




Maßzeichnung
Package Outlines



Maße in mm (inch) / Dimensions in mm (inch).

Empfohlenes Lötpaddesign
Recommended Solder Pad

Wellenlöten (TTW)
TTW Soldering




Maße in mm (inch) / Dimensions in mm (inch).

Lötbedingungen**Soldering Conditions****Wellenlöten (TTW)**

(nach CECC 00802)

TTW Soldering

(acc. to CECC 00802)



Published by
OSRAM Opto Semiconductors GmbH
Leibnizstrasse 4, D-93055 Regensburg
www.osram-os.com

© All Rights Reserved.

The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances. For information on the types in question please contact our Sales Organization.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Components used in life-support devices or systems must be expressly authorized for such purpose! Critical components¹, may only be used in life-support devices or systems² with the express written approval of OSRAM OS.

¹ A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or effectiveness of that device or system.

² Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or maintain and sustain human life. If they fail, it is reasonable to assume that the health of the user may be endangered.

EU RoHS and China RoHS compliant product



此产品符合欧盟 RoHS 指令的要求；

按照中国的相关法规和标准，不含有毒有害物质或元素。