



JKL PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) TYP.	OPERATING LAMP VOLTAGE VL (Vrms) TYP.	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF2698-20B	98±2.0	5,400°k x = .336 y = .353	690 @ 0°C	275	5 ± 1	30,000 TYP.	35,000 AVG.
BF26188-20B	188±3.0		1115 @ 0°C	405			
BF26214-20B	214±2.0		1150 @ 0°C	460			
BF26285-20B	285±1.5		1525 @ 0°C	610			
BF26318-20B	318±1.5		1710 @ 0°C	685			
BF26360-20B	360±1.5		1940 @ 0°C	775			

NOTES:

\* RATED LIFE IS DEFINED AS THE POINT WHICH INTENSITY BECOMES 50% OF THE INITIAL RATING.

RATING AT 25°C UNLESS OTHERWISE SPECIFIED.

			<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- REF.		<b>JKL COMPONENTS CORPORATION</b>			
DRAWN BY L. WENGSTROM			APPVD BY L.R.		DATE 3/25/08		TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>	
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			SIZE <b>A</b>		FSCM NO. <b>55335</b>		DRAWING NO. <b>BF 26-20B</b>	
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			SCALE NONE		RELEASED DATE 8/14/03		REVISION DATE 3/25/08	
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		REV. NO. <b>D</b>		SHEET 1 OF 1	