


JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) MINIMUM
BF22180-28B	x = .346 y = .319	1140 @ 0°C	380	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION				
		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP				
B RATED LIFE HRS MINIMUM A CIRCUIT & LAMP VOLTAGE CHANGE RELEASED & CANCEL P-0303-14	7/30/09 7/19/04 9/2/03	DRAWN BY L. WENGSTROM	APPVD BY DATE L.R. 7/30/09	SIZE A	FSCM NO. 55335	DRAWING NO. BF22180-28B
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 9/2/03	REVISION DATE 7/30/09	REV. NO. B	SHEET 1 OF 1