


JKL LAMP PART NO. (REFERENCE)	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms) @ 25°C	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) MINIMUM
CF26349-28B	x = .325 y = .295	1715	730	5 ± 1	30,000 ± 3000	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>					
					TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>							
<b>A</b> RATED LIFE HRS MINIMUM HEADING & 20,000 RELEASED & CANCEL P-0210-08 & BF26349-28B			DRAWN BY L. WENGSTROM		APPVD BY DATE L.R. 8/5/09		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>CF26349-28B</b>			
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>		RELEASED DATE <b>1/29/03</b>	REVISION DATE <b>8/5/09</b>	REV. NO. <b>A</b>	SHEET <b>1 OF 1</b>		