



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 9450°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF20305-24B	x = .285 y = .289	1013 @ 0°C	695	5 ± 1	28,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION				
	DRAWN BY L. WENGSTROM	APPVD BY P.A.	DATE 12/5/05	SIZE A	FSCM NO. 55335	DRAWING NO. BF20305-24B
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 12/5/05	REVISION DATE	REV. NO.	SHEET 1 OF 1