


JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 5600°K (RGB)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF4142-20B	x = 0.337 ± .03 y = 0.368 ± .03	800	260	5	9,500 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
					TITLE SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP							
A ADD x & y COORDINATED RELEASED TO CAD			DRAWN BY L. WENGSTROM		APP'VD BY DATE L. R. 7/5/06		SIZE A		FSCM NO. 55335		DRAWING NO. BF4142-20B	
REV. NO. DESCRIPTION/ECO NUMBER APP'VD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 9/17/02		REVISION DATE 7/5/06		REV. NO. A SHEET 1 OF 1	