



JKL LAMP PART NO.	COLOR WHITE 6900°KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) MINIMUM
BF20125-28B	x = .325 y = .295	700 @ 0°C	280	5	38,000 TYP.	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	<b>JKL COMPONENTS CORPORATION</b>					
	DRAWN BY L. WENGSTROM	APPVD BY L.R.	DATE 7/30/09	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF20125-28B</b>	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 4/22/04	REVISION DATE 7/30/09	REV. NO. <b>A</b>	SHEET 1 OF 1