



JKL LAMP PART NUMBER	COLOR 6900°KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (Cd/m <sup>2</sup> )	*RATED LIFE (HRS)
CF20277-28B	x = .325 y = .295	1560 @ 0°C	625 @ 5mA	5.0 TYP.	38,000 TYP.	20,000 MIN. 40,000 AVG.

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION		<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>			
		TITLE <b>MINIATURE COLD CATHODE          FLUORESCENT LAMP</b>					
DRAWN BY <b>L. WENGSTROM</b>		APP'VD BY DATE <b>J.K. 4/22/04</b>		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>CF20277-28B</b>	
RELEASED & CANCEL P-0404-13 4/22/04		APP'VD DATE		SCALE <b>NONE</b>		RELEASED DATE <b>4/22/04</b>	
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		REVISION DATE	REV. NO.	
						SHEET <b>1 of 1</b>	