



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 8800°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) AVERAGE
BF3240-24B	x = .285 y = .278	1240	495	5 ± 1	28,000 ± 10%	40,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>			
		DRAWN BY <b>L. WENGSTROM</b>		APP'VD BY DATE <b>J.K. 8/4/04</b>		TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>	
<b>A</b> ELECTRICAL RATING CHANGES RELEASE AND CANCEL P-0105-05		8/4/04 8/1/01		SIZE <b>A</b> FSCM NO. <b>55335</b>		DRAWING NO. <b>BF3240-24B</b>	
REV. NO. DESCRIPTION/ECO NUMBER APP'VD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>		RELEASED DATE <b>8/1/01</b> REVISION DATE <b>8/4/04</b> REV. NO. <b>A</b> SHEET <b>1 OF 1</b>	