


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (Cd/m ²)	*RATED LIFE (HRS)
CF20325-24B	8400 Kelvin x = .290 REF. y = .305 REF.	**1830 MAX.	735 @ 5mA	5.0 TYP. 7.0 MAX.	46,000 TYP.	20,000 MIN. 40,000 AVG.

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

**MAY BE HIGHER WHEN MOUNTED IN METAL RAIL AND USING INPUT HARNESS, REF. 2250 Vrms Max. @ 0 C.

METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
				TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
DRAWN BY L. WENGSTROM		APPVD BY J.K.		DATE 5/3/05		SIZE A	
FSCM NO. 55335		DRAWING NO. CF20325-24B					
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 4/15/04		REVISION DATE 5/3/05	
REV. NO.		DESCRIPTION/ECO NUMBER		APPVD DATE		REV. NO. A	
A CHANGE BRIGHTNESS TO 46,000 TYP. RELEASED		5/3/05 4/15/04		SHEET 1 OF 1			