



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF23312-24B	x = 0.287 y = 0.284	1100 @ 0°C	618	6 ± 1	50,000 ± 20%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE
C	X Y AND BRIGHTNESS RATINGS CHANGE	11/12/08
B	BRIGHTNESS ±10% TO ±20%	6/13/08
A	CHANGE + ADDITIONAL DIMENSIONS	3/21/08
	RELEASE & CANCEL P-0701-05	2/21/07

METRIC THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0	JKL COMPONENTS CORPORATION			
		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
DRAWN BY L. WENGSTROM	APPVD BY L.R.	DATE 11/12/08	SIZE A	FSCM NO. 55335	DRAWING NO. BF23312-24B
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 2/21/07	REVISION DATE 11/12/08
				REV. NO. C	SHEET 1 OF 1