


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF24438-33B	WHITE 10,000°k x = .283 y = .299	1400 TYP. @ 0°C 1820 MAX.	835	5.0		20,000
				6.5±5%	38,000±10%	

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 1.0 2 PL +/- 0.05 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
				TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
DRAWN BY L. WENGSTROM		APPVD BY L.R.		DATE 7/30/09		SIZE A	
FSCM NO. 55335		DRAWING NO. BF24438-33B		SCALE NONE		RELEASED DATE 3/17/04	
REVISION DATE 7/30/09		REVISION DATE 7/30/09		REV. NO. A		SHEET 1 OF 1	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED							