



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF4183-20B	183mm	RGB HIGH OUTPUT WHITE 5600° KELVIN	900 @ 0°C	365	5 ± 1	15,000±10%	20,000
BF4220-20B	220mm		1,000 @ 0°C	405	5 ± 1	15,000±10%	20,000
BF4418-20B	418mm		1,400 @ 0°C	765	5 ± 1	15,000±10%	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		COMPONENTS CORPORATION					
DRAWN BY		APPVD BY DATE		SIZE	FSCM NO.	DRAWING NO.			
L. WENGSTROM		J.K. 9/17/02		A	55335	BF 4-20B			
RELEASED TO CAD		9/17/02		- CAD DRAWING -					
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	MANUAL REVISIONS NOT PERMITTED		SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
					NONE	9/17/02			1 OF 1