


JKL LAMP PART NO. (REF.)	COLOR WHITE 4200°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) MINIMUM
BF20137-26B	x = .372 y = .371	1125 @ 0°C	320	5	42,000 ± 15%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<b>METRIC</b>  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	<b>JKL COMPONENTS CORPORATION</b>					
		TITLE <b>MINIATURE COLD CATHODE          FLUORESCENT LAMP</b>					
<b>A</b> RATED LIFE HRS MINIMUM RELEASE AND CANCEL P-0310-09	7/30/09 2/23/05	DRAWN BY L. WENGSTROM	APPVD BY L.R.	DATE 7/30/09	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF20137-26B</b>
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>		RELEASED DATE <b>2/23/05</b>	REVISION DATE <b>7/30/09</b>	REV. NO. <b>A</b>	SHEET <b>1 OF 1</b>