



JKL LAMP PART NO.	COLOR RGB WHITE REF. 9700°k	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) MINIMUM
BF20185-25B	x = 0.28 ± 0.02 y = 0.26 ± 0.02	1050 @ 0°C	420	5	35,000 TYP.	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

NOTE 1: MERCURY (Hg) CONTENT: 2.4mg/LAMP MAX.

 THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	<b>JKL COMPONENTS CORPORATION</b>				
		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP				
DRAWN BY L. WENGSTROM	APPVD BY L.R.	DATE 7/30/09	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF20185-25B</b>	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 11/23/05	REVISION DATE 7/30/09	
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	REV. NO.	<b>A</b>	SHEET 1 OF 1	