



JKL LAMP PART NO. (REFERENCE)	COLOR LCD HIGH OUTPUT WHITE 6700°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26409-31B	x = 0.310 y = 0.321	1540	730	5 ± 1	36,000 ± 15%	20,000 MIN. 40,000 AVG.

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION			
	TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP				
DRAWN BY L. WENGSTROM	APPVD BY LARRY R.	DATE 8/14/06	SIZE A	FSCM NO. 55335	DRAWING NO. BF26409-31B
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 8/14/06	REVISION DATE
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	REV. NO.	SHEET 1 OF 1	