


NOTE: End Cap to be impression stamped with "JKL and applicable PART NUMBER."

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
GF540	6.0	.100	.10	1.26	10,000	C-8
GF550	6.0	.200	.40	5.03	5,000	C-8
GF570	6.3	.250	.64	8.04	10,000	C-8
GF560	6.3	.300	.64	8.04	10,000	C-8
GF660	8.0	.150	.40	5.03	10,000	C-8
GF665	8.0	.200	.25	3.14	10,000	C-8
GF670	8.0	.250	.64	8.04	10,000	C-8
GF680	8.0	.300	.90	11.31	10,000	C-8
GF710	12.0	.100	.23	2.89	10,000	C-8
GF780	12.0	.150	.70	9.00	5,000	C-8
GF740	12.6	.300	.64	8.04	5,000	C-8

METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/-		JKL COMPONENTS CORPORATION			
DRAWN BY		APPV'D BY DATE		SIZE	PSCM NO.	DRAWING NO.	
L. WENGSTROM		ED 3/1/01		A	55335	FUSE GF SERIES T-2	
- CAD DRAWING -				SCALE	RELEASED DATE	REVISION DATE	
MANUAL REVISIONS NOT PERMITTED				NONE	3/1/01		
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	REV. NO.	SHEET	1 of 1		
RELEASED		3/1/01					