


| JKL LAMP NUMBER | VOLTS RATED | AMPS $\pm 10\%$ | MSCP $\pm 25\%$ | LUMENS $\pm 25\%$ | AVERAGE LIFE HRS. | FILAMENT TYPE |
|-----------------|-------------|-----------------|-----------------|-------------------|-------------------|---------------|
| SM0640G         | 6.0         | .040            | .048            | 0.60              | 5,000             | C-2V          |
| SM06200G        | 6.0         | .200            | .334            | 4.20              | 5,000             | C-2R          |
| SM1220G         | 12.0        | .020            | .032            | 0.40              | 5,000             | C-2V          |
| SM1250G         | 12.0        | .050            | .160            | 2.01              | 5,000             | C-2V          |
| SM12100G        | 12.0        | .100            | .255            | 3.21              | 5,000             | C-2V          |
| SM2420G         | 24.0        | .020            | .064            | 0.80              | 5,000             | C-2F          |
| SM2450G         | 24.0        | .050            | .279            | 3.51              | 5,000             | C-2F          |
| SM3020G         | 30.0        | .020            | .104            | 1.31              | 5,000             | C-2F          |
| SM3050G         | 30.0        | .050            | .319            | 4.00              | 5,000             | C-2F          |
| SM4840G         | 48.0        | .040            | .358            | 4.50              | 5,000             | CC-2F         |
| SM6020G         | 60.0        | .020            | .184            | 2.30              | 5,000             | CC-2F         |

|  |   |                                   |                                    |                                 |                          |                                       |
|--|---|-----------------------------------|------------------------------------|---------------------------------|--------------------------|---------------------------------------|
| <b>METRIC</b><br><br>THIRD ANGLE PROJECTION | DIMENSIONS ARE IN MILLIMETERS<br>TOLERANCE UNLESS OTHERWISE SPECIFIED<br>1 PL +/- 0.2<br>2 PL +/- 0 | <b>JKL COMPONENTS CORPORATION</b> |                                    |                                 |                          |                                       |
|  | TITLE<br><b>T-2 TELEPHONE SLIDE BASE T6.8</b>   |                                   |                                    |                                 |                          |                                       |
| B DELETE PART NO. SM2845G<br>A ADD SM3050G & SM6020G<br>RELEASED   | 10/9/01<br>8/31/00<br>8/16/00   | DRAWN BY<br><b>L. WENGSTROM</b>   | APPVD BY DATE<br><b>QC 10/9/01</b> | SIZE<br><b>A</b>                | FSCM NO.<br><b>55335</b> | DRAWING NO.<br><b>SLIDE BASE T6.8</b> |
| - CAD DRAWING -<br>MANUAL REVISIONS NOT PERMITTED  |   | SCALE<br><b>NONE</b>              | RELEASED DATE<br><b>8/16/00</b>    | REVISION DATE<br><b>10/9/01</b> | REV. NO. <b>B</b>        | SHEET <b>1</b> OF <b>1</b>            |