



JKL LAMP NUMBER	VOLTS RATED	AMPS $\pm 10\%$	MSCP $\pm 25\%$	LUMENS $\pm 25\%$	AVERAGE LIFE HRS.	FILAMENT TYPE AND POSITION
1034	12.8	1.80	32.0	402.2	200	C-2R POSITION #2 = 2 FILAMENTS
	14.0	.59	3.0	37.7	5,000	C-2R POSITION #1 = 1 FILAMENT
1157	12.8	2.10	32.0	402.2	1,200	C-2R POSITION #2 = 2 FILAMENTS
	14.0	.59	3.0	37.7	3,000	C-2R POSITION #1 = 1 FILAMENT

		 THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>									
						TITLE <b>S-8 DOUBLE CONTACT INDEX BAYONET BASE LAMP</b>									
<b>A</b> DIM. CHNG ON CONTACTS TO 6.48/7.08 RELEASED AS CAD		5/18/01 5/9/01		DRAWN BY L. WENGSTROM		APPV'D BY QC		DATE 5/18/01		SIZE <b>A</b>		FSCM NO. <b>55335</b>		DRAWING NO. <b>BAYONET DOUBLE CONTACT INDEX S-8</b>	
REV. NO.		DESCRIPTION/ECO NUMBER		APPV'D DATE		SCALE NONE		RELEASED DATE 5/9/01		REVISION DATE 5/18/01		REV. NO. <b>A</b>		SHEET 1 OF 1	