



**ATTENTION**  
OBSERVE PRECAUTIONS  
FOR HANDLING  
ELECTROSTATIC  
DISCHARGE  
SENSITIVE  
DEVICES

Part Number: APHBM2012PBASURKC

Blue  
Hyper Red

### Features

- 2.0mmx1.25mm SMT LED, 0.45mm max. thickness.
- Bi -color, low power consumption.
- Wide viewing angle.
- Ideal for backlight and indicator.
- Package : 2000pcs / reel.
- Moisture sensitivity level : level 3.
- RoHS compliant.

### Description

The Blue source color devices are made with InGaN on SiC Light Emitting Diode.




The Hyper Red source color devices are made with Al-GaN on GaAs substrate Light Emitting Diode.

Static electricity and surge damage the LEDs.

It is recommended to use a wrist band or anti-electrostatic glove when handling the LEDs.

All devices, equipment and machinery must be electrically grounded.

### Package Dimensions



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.1(0.004")$  unless otherwise noted.
3. Specifications are subject to change without notice.
4. The device has a single mounting surface. The device must be mounted according to the specifications.



## Selection Guide

| Part No.          | Dice                | Lens Type   | Iv (mcd) [2]<br>@ 20mA |      | Viewing<br>Angle [1] |
|-------------------|---------------------|-------------|------------------------|------|----------------------|
|                   |                     |             | Min.                   | Typ. | 2θ1/2                |
| APHBM2012PBASURKC | Blue (InGaN)        | WATER CLEAR | 18                     | 50   | 120°                 |
|                   | Hyper Red (AlGaInP) |             | 70                     | 220  |                      |

Notes:

1. θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.
2. Luminous intensity/ luminous Flux: +/-15%.

## Electrical / Optical Characteristics at TA=25°C

| Symbol | Parameter                | Device            | Typ.        | Max.     | Units | Test Conditions |
|--------|--------------------------|-------------------|-------------|----------|-------|-----------------|
| λpeak  | Peak Wavelength          | Blue<br>Hyper Red | 468<br>650  |          | nm    | IF=20mA         |
| λD [1] | Dominant Wavelength      | Blue<br>Hyper Red | 470<br>630  |          | nm    | IF=20mA         |
| Δλ1/2  | Spectral Line Half-width | Blue<br>Hyper Red | 21<br>28    |          | nm    | IF=20mA         |
| C      | Capacitance              | Blue<br>Hyper Red | 100<br>35   |          | pF    | VF=0V;f=1MHz    |
| VF [2] | Forward Voltage          | Blue<br>Hyper Red | 3.2<br>1.95 | 4<br>2.5 | V     | IF=20mA         |
| IR     | Reverse Current          | Blue<br>Hyper Red |             | 10<br>10 | uA    | VR = 5V         |

Notes:


1. Wavelength: +/-1nm.
2. Forward Voltage: +/-0.1V.

## Absolute Maximum Ratings at TA=25°C






| Parameter                | Blue           | Hyper Red | Units |
|--------------------------|----------------|-----------|-------|
| Power dissipation        | 120            | 75        | mW    |
| DC Forward Current       | 30             | 30        | mA    |
| Peak Forward Current [1] | 100            | 185       | mA    |
| Reverse Voltage          | 5              |           | V     |
| Operating Temperature    | -40°C To +85°C |           |       |
| Storage Temperature      | -40°C To +85°C |           |       |

Note:

1. 1/10 Duty Cycle, 0.1ms Pulse Width.








## APHBM2012PBASURKC Blue



# Kingbright


## Hyper Red



## APHBM2012PBASURKC

Reflow soldering is recommended and the soldering profile is shown below.  
Other soldering methods are not recommended as they might cause damage to the product.


Reflow Soldering Profile For Lead-free SMT Process.




**NOTES:**

1. We recommend the reflow temperature 245°C(+/-5°C). The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.

### Recommended Soldering Pattern (Units : mm; Tolerance: ± 0.1)





### Tape Dimensions (Units : mm)




# Kingbright

## PACKING & LABEL SPECIFICATIONS

## APHBM2012PBASURKC



|  |  |
|--|--|
| <b>Kingbright</b>  |  |
| P/NO: APHBM2012xxx   |  |
| QTY: 2,000 pcs   | Q.C. <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">Q C<br/>xx xx xxxx<br/>PASSED</span> |
| S/N: XXXX  |  |
| CODE: XXX  |  |
| LOT NO:  |  |
| <br>xxxxxxxxxxxxxxxxxxxxxxxx |  |
| RoHS Compliant   |  |