


2.00 [0.079]



ELECTRO-OPTICAL (CHARACTERIST	ICS TA=25	.c	If= 20mA	
PARAMETER	MIN	TYP	MAX	ZTINU	TEST COND
PEAK WAVELENGTH		555		nm	
FORWARD VOLTAGE		2.1	2.5	Vf	
REVERSE VOLTAGE	5.0			V_r	I _r =100μΑ
AXIAL INTENSITY		6		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		110		2x theta	
EMITTED COLOR:	GREEN				

EPOXY LENS FINISH: MILKY WHITE TOP DIFFUSED

LIMITS OF	SAFE	OPERATION	ΑT	25°C	
-----------	------	-----------	----	------	--

PARAMETER	MAX	UNITS	
PEAK FORWARD CURRENT*	150	mA	
STEADY CURRENT	25	mA	
POWER DISSIPATION	105	mW	
DERATE FROM 25°C	-1.2	m₩/*C	
OPERATING, STORAGE TEMP.	- 40 TO + 85	•c	
SOLDERING TEMP.	+ 260	· c	
2.0mm FROM BODY		3 SEC. MAX	
* t<10uS			

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.035). LEAD SZE=±0.05 (±0.002), LEAD

PART NUMBER REV. Α SSL-LX2573PGW-TD 2mm x 5mm RECTANGULAR, 555nm PURE GREEN LED,

MILKY WHITE TOP DIFFUSED LENS.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF
LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WHITNE BY LUMEX
INC., THE HOLDER OF THIS DOCUMENT ISAIL KEEP ALL INFORMATION
CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR
IN PART FROM DISCLOSURE AND DISSEMBATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR NAMY YEARS OF EXPERENCE OF DATA ACCUMULATION INDICATE THAT

SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.

PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

CHECKED BY: APPROVED BY: DATE: DRAWN BY: 5.14.92 PAGE: 1 OF 1 SCALE: BC

Downloaded from Elcodis.com electronic components distributor