


1-Watt SMD 6mm (120° Viewing Angle)

OVSPxBCR4 Series

- Robust energy-efficient design with long operating life
- Low thermal resistance
- High luminous intensity
- Optional optics to suit application




The **OVSPxBCR4 Series** is an energy-efficient packaged LED source that offers high luminance, and a long operating lifespan. These devices offer a 120° viewing angle and an ultra-low profile (1.5mm) making them highly suitable for conventional lighting and specialized applications. Optional optics are offered to suit application. Please contact OPTEK for more information.




Applications

- Automotive exterior and interior lighting
- Architectural indoor and outdoor lighting
- General lighting
- Electronic signs and signals

Part Number	Viewing Angle	Material	Emitted Color	Typical Luminous Flux (lm)	Lens Color
OVSPBBCR4	120°	InGaN	Blue	20	Water Clear
OVSPGBCR4		InGaN	Green	54	Water Clear
OVSPRBCR4		AllnGaP	Red	42	Water Clear
OVSPYBCR4		AllnGaP	Yellow	34	Water Clear
OVSPW1BCR4		InGaN	White	90	Water Clear
OVSPWWBCR4		InGaN	Warm White	50	Water Clear



DIMENSIONS ARE IN INCHES [MM]
GENERAL TOLERANCES ±.004 [0.10]



BLUE, GREEN

PIN 1	PIN 2
CATHODE	ANODE




RED, YELLOW

PIN 1	PIN 2
ANODE	CATHODE



WHITE, WARM WHITE



DO NOT LOOK DIRECTLY AT LED WITH UNSHIELDED EYES OR DAMAGE TO RETINA MAY OCCUR.

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

1-Watt SMD 6mm OVSPxBCR4 Series



Absolute Maximum Ratings $T_A = 25^\circ\text{C}$

	Red, Yellow	Green, Blue	White	Warm White
DC Forward Current	400mA	350mA	350mA	350mA
Peak Pulsed Forward Current ¹	500mA	1000mA	1000mA	1000mA
Reverse Voltage	12V	Not designed for reverse bias		
Junction Temperature ²	125°C	120°C	150°C	125°C
Power Dissipation	1200mW			
Storage and Operating Temperature	-40° ~ +100 °C			
MSL Level (IPC/JEDEC J-STD-020C)	2a / 672 Hrs			
ESD Threshold (HBM)	Class 2			

Notes:

1. Pulse width $t_p \leq 10\mu\text{s}$, Duty cycle = 0.1
2. Thermal conductivity = 20K/W for red, yellow, green, blue; and 18K/W for white

Optical and Electrical Characteristics—Red, Yellow ($I_F = 400\text{ mA}$, $T_A = 25^\circ\text{C}$)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	
V_F	Forward Voltage	2.2	2.5	2.8	V	
Φ	Luminous Flux	Red	33	42	54	lm
		Yellow	27	34	42	lm
λ_D	Dominant Wavelength	Red	620	625	630	nm
		Yellow	585	591	597	nm
I_R	Reverse Current	----	100	----	μA	
$2\Theta_{1/2}$	50% Power Angle	----	120	----	deg	

Optical and Electrical Characteristics—Blue, Green ($I_F = 350\text{ mA}$, $T_A = 25^\circ\text{C}$)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	
V_F	Forward Voltage	----	3.6	4.0	V	
Φ	Luminous Flux	Blue	13.5	20	27	lm
		Green	38	48	60	lm
λ_D	Dominant Wavelength	Blue	460	470	475	nm
		Green	520	530	535	nm
$2\Theta_{1/2}$	50% Power Angle	----	120	----	deg	

Optical and Electrical Characteristics—White, Warm White ($I_F = 350\text{ mA}$, $T_A = 25^\circ\text{C}$)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	
V_F	Forward Voltage	3.0	3.5	4.0	V	
Φ	Luminous Flux	White	67	90	113	lm
		Warm White	39	50	67	lm
$2\Theta_{1/2}$	50% Power Angle	----	120	----	deg	

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

1-Watt SMD 6mm

OVSPxBCR4 Series

Standard Bins

LEDs are sorted to the luminous flux (Φ) and the dominant wavelength (nm) bins shown. Each reel consists of a single intensity bin and a single color bin. Orders are filled utilizing all of the intensity bins or color bins listed in the following tables. Optek will not accept orders for single intensity bins or single color bins.

Luminous Intensity (I_v) @ 400mA

Red: OVSPRBCR4		
Code	Min (lm)	Max (lm)
AC	33	42
AD	42	54

Yellow: OVSPYBCR4		
Code	Min (lm)	Max (lm)
AB	27	34
AC	34	42

Luminous Flux (Φ) @ 350mA (lm)

Blue: OVSPBBCR4		
Code	Min (lm)	Max (lm)
Z1	13.5	16.8
Z2	16.8	21.5
AA	21.5	27

Green: OVSPGBCR4		
Code	Min (lm)	Max (lm)
AD	38	48
AE	48	60
AF	60	

Dominant Wavelength (nm)


Red: OVSPRBCR4	
Full	620 - 630 nm

Blue: OVSPBBCR4	
A0	460 - 465 nm
A	465 - 470 nm
B	470 - 476 nm

Yellow: OVSPYBCR4	
A	585 - 588 nm
B	588 - 591 nm
C	591 - 594 nm
D	594 - 597 nm

Green: OVSPMBCR4	
A0	520 - 525 nm
A	525 - 530 nm
B	530 - 535 nm

Beam Angle — All Colors




OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

1-Watt SMD 6mm OVSPxBCR4 Series



Standard Bins ($I_F = 350\text{mA}$)

LEDs are sorted to the luminous flux (Φ) and the dominant wavelength (nm) bins shown. Each reel consists of a single intensity bin and a single color bin. Orders are filled utilizing all of the intensity bins or color bins listed in the following tables. Optek will not accept orders for single intensity bins or single color bins.



Φ	Luminous Flux (lm)	
	Bin	Max
T2	67	76
T3	76	87
U2	87	99
U3	99	113

Chromaticity Coordinates (x, y)

Rank	YO				YA															
Cx	0.274	0.303	0.308	0.283	0.283	0.308	0.311	0.290												
Cy	0.301	0.333	0.311	0.284	0.284	0.311	0.293	0.270												
Rank	XM				XN				XO				XP							
Cx	0.301	0.314	0.315	0.303	0.303	0.315	0.316	0.305	0.305	0.316	0.318	0.308	0.308	0.318	0.320	0.311				
Cy	0.342	0.353	0.343	0.333	0.333	0.343	0.332	0.322	0.322	0.332	0.319	0.311	0.311	0.319	0.301	0.293				
Rank	WM				WN				WO				WP				WQ			
Cx	0.314	0.329	0.329	0.315	0.315	0.329	0.329	0.316	0.316	0.329	0.329	0.318	0.318	0.329	0.329	0.319	0.319	0.329	0.330	0.320
Cy	0.353	0.366	0.354	0.343	0.343	0.354	0.343	0.332	0.332	0.343	0.330	0.319	0.319	0.330	0.319	0.310	0.310	0.310	0.319	0.301
Rank	VM				VN				VO				VP							
Cx	0.329	0.348	0.347	0.329	0.329	0.347	0.346	0.329	0.329	0.346	0.344	0.329	0.329	0.344	0.343	0.329				
Cy	0.366	0.383	0.368	0.354	0.354	0.368	0.357	0.343	0.343	0.357	0.343	0.330	0.330	0.343	0.331	0.319				
Rank	UM				UN				UO				UP							
Cx	0.348	0.367	0.364	0.347	0.347	0.364	0.362	0.346	0.346	0.362	0.359	0.344	0.344	0.359	0.357	0.343				
Cy	0.383	0.400	0.383	0.368	0.368	0.383	0.372	0.357	0.357	0.372	0.356	0.343	0.343	0.356	0.343	0.331				


OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

1-Watt SMD 6mm OVSPxBCR4 Series



Standard Bins ($I_F = 350\text{mA}$)

LEDs are sorted to the luminous flux (Φ) and the dominant wavelength (nm) bins shown. Each reel consists of a single intensity bin and a single color bin. Orders are filled utilizing all of the intensity bins or color bins listed in the following tables. Optek will not accept orders for single intensity bins or single color bins.



Φ	Luminous Flux (lm)	
	Bin	Max
R2	39.8	45.2
R3	45.2	51.7
S2	51.7	59.0
S3	59.0	67.2


Chromaticity Coordinates (x, y)

Rank	QM				QN				QO				QP			
Cx	0.421	0.437	0.430	0.415	0.415	0.430	0.423	0.409	0.409	0.423	0.416	0.402	0.402	0.416	0.409	0.397
Cy	0.433	0.438	0.421	0.416	0.416	0.421	0.405	0.400	0.400	0.405	0.387	0.381	0.382	0.387	0.372	0.367
Rank	PM				PN				PO				PP			
Cx	0.437	0.452	0.444	0.430	0.430	0.444	0.436	0.423	0.423	0.436	0.428	0.416	0.416	0.428	0.421	0.409
Cy	0.438	0.443	0.426	0.421	0.421	0.426	0.409	0.405	0.405	0.409	0.392	0.387	0.387	0.392	0.377	0.372
Rank	NM				NN				NO				NP			
Cx	0.452	0.469	0.460	0.444	0.444	0.460	0.451	0.436	0.436	0.451	0.443	0.428	0.428	0.443	0.435	0.421
Cy	0.443	0.448	0.431	0.426	0.426	0.431	0.414	0.409	0.409	0.414	0.397	0.392	0.392	0.397	0.382	0.377
Rank	MM				MN				MO				MP			
Cx	0.463	0.487	0.477	0.460	0.460	0.477	0.467	0.451	0.451	0.467	0.458	0.443	0.443	0.458	0.449	0.435
Cy	0.448	0.454	0.437	0.431	0.431	0.437	0.420	0.414	0.414	0.420	0.403	0.397	0.397	0.403	0.388	0.382


OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Typical Electro-Optical Characteristics Curves—Red, Yellow


Relative Intensity Vs Forward Current



Forward Voltage Vs Forward Current




Maximum Current Vs Solder Point Temperature




OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Typical Electro-Optical Characteristics Curves—Blue, Green


Wavelength Vs Forward Current




Relative Flux Vs Forward Current




Forward Current Vs Forward Voltage



Forward Current Vs Ambient Temperature (R_{ja}=40KW)







Forward Current Vs Solder Point Temperature




OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.


Typical Electro-Optical Characteristics Curves—White



Forward Current Vs Ambient Temperature (Rja=40K/W)







Forward Current Vs Solder Point Temperature




OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.


Typical Electro-Optical Characteristics Curves—Warm White



Forward Current Vs Ambient Temperature (Rja=40K/W)




Forward Current Vs Solder Point Temperature




OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Solder Pad Design

Metal core circuit board (MCPCB) is highly recommended for high density applications.




Solder Paste Pattern




Copper Pattern

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Recommended Sn-Pb IR-Reflow Soldering Profile.




Recommended Pb Free IR-Reflow Soldering Profile.




OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

1-Watt SMD 6mm OVSPxBCR4 Series

Reel Dimensions: 13 - inch reel




Carrier Tape Dimensions: Loaded quantity 2000 pieces per reel



DIMENSIONS ARE IN INCHES [MM]
 TOLERANCES ARE $\pm .004$ [10] UNLESS OTHERWISE SPECIFIED

Moisture Resistant Packaging



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.