UNCONTROLLED DOCUMENT PART NUMBER REV. SSF-LXH400XX SSF-IXH400XX 25.00±0.50 - 2.50±0.50 [0.098±0.020] Ø4.80 [Ø0.189] [0.984±0.020] (4 PLS.) 6.36 [0.250] 9.00 [0.354] (3 PLS.) 6.00 [0.236] 3.18±0.75 [0.125±0.030] ANDDE TYP. 2.54 [0.100] THIS SIDE (4 PLS.) 0.50 [0.020] SQR. (8 PLS.) - 21.62 [0.851] **-**5.50±1.00 [0.217±0.039] *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: $X=\pm1$ (±0.039), $X.X=\pm0.5$ (±0.020), $X.XX=\pm0.25$ (±0.010), $X.XXX=\pm0.127$ (±0.005). LEAD SIZE= ±0.05 (±0.002), LEAD LENGTH= ±0.75 (±0.030). MIN= ±0.00 PRECISION MAX= ±0.00 MAX= ±0.00 PRECISION MAX= ±0 CONFIDENTIAL INFORMATION THE INFORMATION CONTINUED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. 290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw PART NUMBER REV. SSF-LXH400XX

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT
SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

CHECKED BY: APPROVED BY: DATE:

1 OF 1

N/A

PAGE: SCALE:

DRAWN BY:

FAULT INDICATOR LED.