




5650 Series T-1 Right Angle LED Assembly

DESCRIPTION AND FEATURES



Features

- T-1 size right angle block preassembled and tested.
- Super Brite and High Brite LEDs.
- High light output - diffused lens.

Note: Alternate LEDs are also available in this package as a standard variation.

Mounting hole pattern on page 1-X4.

ELECTRO-OPTICAL CHARACTERISTICS AND RATINGS

Part Number	Emitted Color	Typical Intensity (mcd)	Rated Current (mA)	Continuous Forward Current Max. (mA)	Forward Voltage		Reverse Breakdown Voltage Min. (V)	Peak Wavelength (nm)
					Typ. (V)	Max. (V)		
5650F1	Red	10	10	30	2.0	3.0	5	650
5650F3	Amber	7	10	25	2.0	3.0	5	603
5650F5	Green	16	10	30	2.2	3.0	5	562
5650F7	Yellow	6.3	10	30	2.1	3.0	5	585
5650F1LC	Red	2.5	2.0	7	1.8	2.2	5	635
5650F5LC	Green	2.1	2.0	7	1.8	2.2	5	565
5650F7LC	Yellow	1.8	2.0	7	1.9	2.7	5	583
5652F1-5V	Red	8.0	13.0	20	5	7.5	5	655
5652F3-5V	Amber	8.0	10.0	15	5	7.5	5	583
5652F5-5V	Green	8.0	10.0	15	5	7.5	5	565

147 Central Avenue
Hackensack, NJ 07601
Phone: (201) 489-8989
Fax: (201) 489-6911

18703 Dix Toledo Road
Brownstown, MI 48193

Saret Zone Franca, Edificio B
Alajuela Costa Rica

E-mail: sales@chml.com • Web Site: www.chml.com

Chicago Miniature Lighting, LLC reserves the right to make specification revisions that enhance the design and/or performance of the product