




5894S Series Panel Mounted LED Indicator Light

DESCRIPTION AND FEATURES



Features

- 4 LEDs stack mounted in single block saves space and assembly time.
- Super Brite light output
- Standoffs prevent flux entrapment.
- Black plastic mounting block for high contrast ratio.
- Meets UL 94V-0 and Bellcore flammability specifications.
- Assembly can also be supplied in various color combinations. Call factory for details.

ELECTRO-OPTICAL CHARACTERISTICS AND RATINGS

Part Number	Emitted Color	Typical Intensity (mcd)	Rated Current (mA)	Continuous Forward Current Max. (mA)	Forward Voltage		Reverse Breakdown Voltage Min. (V)	Peak Wavelength (nm)	Peak Forward Current @ 1ms-300 PPS (A)
					Typ. (V)	Max. (V)			
5894S 1;1;1;1	Red	10	10	30	2.2	3.0	5	650	-
5894S 5;5;5;5	Green	16	10	30	2.3	3.0	5	562	-
5894S 7;7;7;7	Yellow	6.3	10	30	2.2	3.0	5	585	-

147 Central Avenue
 Hackensack, NJ 07601
 Phone: (201) 489-8989
 Fax: (201) 489-6911

18703 Dix Toledo Road
 Brownstown, MI 48193

Saret Zone Franca, Edificio B
 Alajuela Costa Rica

E-mail: sales@chml.com • Web Site: www.chml.com

Chicago Miniature Lighting, LLC reserves the right to make specification revisions that enhance the design and/or performance of the product