



J	Ø .116 ±.002 WAS Ø .1167-.113.	M.C.	
I	ADDED NOTE 3: .060 (NOTE 3), & 1.100 ±.002 AND Ø .1167-.113 WAS Ø .116 ±.00107-.0013.	M.C. L.R.	7-11-96
H	.550±.005-.008 WAS .550 ±.005.	M.C. D.C.	10-6-95
G	IN DETAIL "A" Ø .116 ±.0011	M.C. M.O.	9-9-94
F	Ø .113±.001 WAS Ø .115±.000-.002	M.C. M.C.	3-7-94
E	1.080 ±.010-.005 WAS 1.05 & 1.23 WAS 1.20.	M.C. M.C.	3-1-94
D	.81 WAS .810.	M.C. M.C.	2-9-94
LTR ECR NO.		REVISIONS	DRW. APP. DATE
THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE PRIOR WRITTEN CONSENT OF DIALIGHT.			
SCALE	2:1	DATE	9-21-93
CUSTOMER DRAWING NO.		DWG. REV.	
C-15817		J	
TITLE LIGHTPIPE ARRAY, RJ45			
PART NUMBER		515-1022	
Dialight			
1913 Atlantic Ave.			
Manasquan, NJ 08736			
FSCM	83330		

- NOTES:
1. COMPONENT TO BE MOLDED IN A WATER CLEAR TRANSMISSIVE POLYCARBONATE.
 2. RECOMMENDED PLACEMENT OF LED.
 3. Ø .116 ±.002 TO BE MAINTAINED FROM SURFACE -A- TO .06, MEASURED AT HIGHEST SERRATION.